



K821K10C0GF5TL2 Information

Part Number K821K10C0GF5TL2

Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 820PF 50V C0G/NP0 RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

www.flaiseger.com

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









K821K10C0GF5TL2 Specifications

Manufacturer Part Number K821K10C0GFSTL2 Manufacturer Vishay BC Components Category Capacitors Package Radial Series Mono-Kap? K Capacitance 820pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -5°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight		
Category Capacitors Package Radial Series Mono-Kap? K Capacitance 820pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Manufacturer Part Number	K821K10C0GF5TL2
Package Radial Series Mono-Kap? K Capacitance 820pF Tolerance ±10% Voltage - Rated 50V Coperating Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Manufacturer	Vishay BC Components
Package Radial Series Mono-Kap? K Capacitance 820pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Category	Capacitors
Series Mono-Kap? K Capacitance 820pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight		Ceramic Capacitors
Capacitance 820pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Package	Radial
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Series	Mono-Kap? K
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.142" L x 0.091" W (3.60mm x 2.30mm)Height - Seated (Max)0.062" (1.58mm)Thickness (Max)-Lead Spacing0.098" (2.50mm)Lead StyleStraight	Capacitance	820pF
Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.142" L x 0.091" W (3.60mm x 2.30mm)Height - Seated (Max)0.062" (1.58mm)Thickness (Max)-Lead Spacing0.098" (2.50mm)Lead StyleStraight	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.142" L x 0.091" W (3.60mm x 2.30mm)Height - Seated (Max)0.062" (1.58mm)Thickness (Max)-Lead Spacing0.098" (2.50mm)Lead StyleStraight	Voltage - Rated	50V
Features - General Purpose - General Purpose - Through Hole - Case - Radial - Case - Case - Radial - Case -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Applications	General Purpose
Package / Case Radial Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Failure Rate	-
Size / Dimension 0.142" L x 0.091" W (3.60mm x 2.30mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.062" (1.58mm) - Under the seated (Max) Lead Style 0.098" (2.50mm) Straight	Package / Case	Radial
Thickness (Max) Lead Spacing 0.098" (2.50mm) Lead Style Straight	Size / Dimension	0.142" L x 0.091" W (3.60mm x 2.30mm)
Lead Spacing 0.098" (2.50mm) Lead Style Straight	Height - Seated (Max)	0.062" (1.58mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.098" (2.50mm)
Report errors?	Lead Style	Straight
		Report errors?

K821K10C0GF5TL2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

K821K10C0GF5TL2 Payment Methods





















K821K10C0GF5TL2 Shipping Methods













If you have any question about K821K10C0GF5TL2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com