

K821K15X7RK5UL2

K821K15X7RK5UL2 Information

Part Number K821K15X7RK5UL2 Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 820PF 200V X7R RADIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

www.flaiseger.com

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









K821K15X7RK5UL2 Specifications

Manufacturer Part Number K821K15X7RK5UL2 Manufacturer Vishay BC Components Category Capacitors Package Radial Series Mono-Kap? K Capacitance 820pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight		
Category Capacitors Package Radial Series Mono-Kap? K Capacitance 820pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Manufacturer Part Number	K821K15X7RK5UL2
Package Radial Series Mono-Kap? K Capacitance 820pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Manufacturer	Vishay BC Components
Package Radial Series Mono-Kap? K Capacitance 820pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Category	Capacitors
Series Mono-Kap? K Capacitance 820pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight		Ceramic Capacitors
Capacitance 820pF Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Package	Radial
Tolerance ±10% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Series	Mono-Kap? K
Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.157" L x 0.098" W (4.00mm x 2.50mm)Height - Seated (Max)0.062" (1.58mm)Thickness (Max)-Lead Spacing0.098" (2.50mm)Lead StyleStraight	Capacitance	820pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style X7R 6-125°C - 125°C - 125°C	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - Straight - Straight - Straight - Seated (Max) - Straight - Straigh	Voltage - Rated	200V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Straight - Straigh	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Applications	General Purpose
Package / Case Radial Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Failure Rate	-
Size / Dimension 0.157" L x 0.098" W (4.00mm x 2.50mm) Height - Seated (Max) 0.062" (1.58mm) Thickness (Max) - Lead Spacing 0.098" (2.50mm) Lead Style Straight	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style 0.062" (1.58mm) - Under Company (2.50mm) Straight	Package / Case	Radial
Thickness (Max) Lead Spacing 0.098" (2.50mm) Lead Style Straight	Size / Dimension	0.157" L x 0.098" W (4.00mm x 2.50mm)
Lead Spacing0.098" (2.50mm)Lead StyleStraight	Height - Seated (Max)	0.062" (1.58mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.098" (2.50mm)
Report errors?	Lead Style	Straight
		Report errors?

K821K15X7RK5UL2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

K821K15X7RK5UL2 Payment Methods





















K821K15X7RK5UL2 Shipping Methods













If you have any question about K821K15X7RK5UL2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com