

### **KA-14DG-24 Information**

Heisener.com

Part Number KA-14DG-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 3PDT 10A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KA-14DG-24 Specifications**

Manufacturer Part Number       KA-14DG-24         Manufacturer       TE Connectivity Potter & Brumfield Relays         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       KA         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       51mA         Coil Voltage       24VDC         Contact Form       3PDT (3 Form C)         Contact Rating (Current)       10A         Switching Voltage       240VAC - Max         Turn On Voltage (Max)       18 VDC         Turn Off Voltage (Min)       -         Operate Time       -         Release Time       -         Features       Insulation - Class B         Mounting Type       Chassis Mount         Termination Style       Solder Lug		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         KA           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         51mA           Coil Voltage         24VDC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         240VAC - Max           Turn On Voltage (Max)         18 VDC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         Insulation - Class B           Mounting Type         Chassis Mount           Termination Style         Solder Lug	Manufacturer Part Number	KA-14DG-24
Package - Series KA Relay Type General Purpose Coil Type Non Latching Coil Current 51mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         KA           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         51mA           Coil Voltage         24VDC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         240VAC - Max           Turn On Voltage (Max)         18 VDC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         Insulation - Class B           Mounting Type         Chassis Mount           Termination Style         Solder Lug	Category	Relays
SeriesKARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current51mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleSolder Lug		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current51mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleSolder Lug	Package	-
Coil TypeNon LatchingCoil Current51mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleSolder Lug	Series	KA
Coil Current51mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time-Release Time-FeaturesInsulation - Class BMounting TypeChassis MountTermination StyleSolder Lug	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time - Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Solder Lug	Coil Type	Non Latching
Contact Form 3PDT (3 Form C)  Contact Rating (Current) 10A  Switching Voltage 240VAC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) -  Operate Time -  Release Time -  Features Insulation - Class B  Mounting Type Chassis Mount  Termination Style Solder Lug	Coil Current	51mA
Contact Rating (Current)  Switching Voltage  240VAC - Max  Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  Release Time  -  Features  Insulation - Class B  Mounting Type  Chassis Mount  Termination Style	Coil Voltage	24VDC
Switching Voltage 240VAC - Max  Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) -  Operate Time -  Release Time -  Features Insulation - Class B  Mounting Type Chassis Mount  Termination Style Solder Lug	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  -  Features  Insulation - Class B  Mounting Type  Chassis Mount  Termination Style  Solder Lug	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  Release Time  Features  Insulation - Class B  Mounting Type  Chassis Mount  Termination Style  Solder Lug	Switching Voltage	240VAC - Max
Operate Time - Release Time - Insulation - Class B Mounting Type Chassis Mount Termination Style Solder Lug	Turn On Voltage (Max)	18 VDC
Release Time - Features Insulation - Class B Mounting Type Chassis Mount Termination Style Solder Lug	Turn Off Voltage (Min)	-
Features Insulation - Class B  Mounting Type Chassis Mount  Termination Style Solder Lug	Operate Time	-
Mounting Type Chassis Mount Termination Style Solder Lug	Release Time	-
Termination Style Solder Lug	Features	Insulation - Class B
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Solder Lug
		Report errors?

### **KA-14DG-24 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **KA-14DG-24 Payment Methods**





















## **KA-14DG-24 Shipping Methods**













If you have any question about KA-14DG-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com