



KA336Z25BU Information



For Reference Only

Part Number KA336Z25BU

Manufacturer Fairchild/ON Semiconductor

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

Description IC VREF SHUNT 2.49V TO92

Package TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KA336Z25BU Specifications

Category Integrated Circuits (ICs) PMIC - Voltage Reference Package TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 2.49V Voltage - Output (Max) - Current - Output 10mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 400µA Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole		
Category Integrated Circuits (ICs) PMIC - Voltage Reference Package TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 2.49V Voltage - Output (Max) - Current - Output 10mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 400μA Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Manufacturer Part Number	KA336Z25BU
PMIC - Voltage Reference Package TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 2.49V Voltage - Output (Max) - Current - Output 10mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 400μA Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Manufacturer	Fairchild/ON Semiconductor
Package TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 2.49V Voltage - Output (Max) - Current - Output 10mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 400μA Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Category	Integrated Circuits (ICs)
Series - Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 2.49V Voltage - Output (Max) - Current - Output 10mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 400µA Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3		PMIC - Voltage Reference
Reference Type Shunt Output Type Fixed Voltage - Output (Min/Fixed) 2.49V Voltage - Output (Max) - Current - Output 10mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 400μA Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Package	TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)
Output Type Fixed Voltage - Output (Min/Fixed) 2.49V Voltage - Output (Max) - Current - Output 10mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 400µA Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package	Series	-
Voltage - Output (Min/Fixed) 2.49V Voltage - Output (Max) - Current - Output 10mA Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 400μA Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Reference Type	Shunt
Voltage - Output (Max) Current - Output 10mA Tolerance ±1% Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package	Output Type	Fixed
Current - Output $10mA$ $10mA$ $10mC$	Voltage - Output (Min/Fixed)	2.49V
Tolerance ±1% Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode 400μA Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Voltage - Output (Max)	-
Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode Operating Temperature Φ°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package	Current - Output	10mA
Noise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode400μAOperating Temperature0°C ~ 70°C (TA)Mounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Tolerance	±1%
Noise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode400μAOperating Temperature0°C ~ 70°C (TA)Mounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Temperature Coefficient	-
Voltage - Input-Current - Supply-Current - Cathode 400μ AOperating Temperature 0° C ~ 70° C (TA)Mounting TypeThrough HolePackage / CaseTO-226-3, TO-92-3 (TO-226AA) (Formed Leads)Supplier Device PackageTO-92-3	Noise - 0.1Hz to 10Hz	-
Current - Supply - Current - Cathode $400\mu A$ Operating Temperature $0^{\circ}C \sim 70^{\circ}C$ (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) TO-92-3	Noise - 10Hz to 10kHz	-
Current - Cathode $400\mu A$ Operating Temperature $0^{\circ}C \sim 70^{\circ}C$ (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Voltage - Input	-
Operating Temperature 0°C ~ 70°C (TA) Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Current - Supply	-
Mounting Type Through Hole Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Current - Cathode	400μΑ
Package / Case TO-226-3, TO-92-3 (TO-226AA) (Formed Leads) Supplier Device Package TO-92-3	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C} \text{ (TA)}$
Supplier Device Package TO-92-3	Mounting Type	Through Hole
	Package / Case	TO-226-3, TO-92-3 (TO-226AA) (Formed Leads)
Report errors?	Supplier Device Package	TO-92-3
		Report errors?

KA336Z25BU Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KA336Z25BU Payment Methods





















KA336Z25BU Shipping Methods













If you have any question about KA336Z25BU, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com