

KA3403D Information



For Reference Only

Part Number KA3403D

Manufacturer ON Semiconductor
Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 9KHZ 14SOIC **Package** 14-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KA3403D Specifications

Manufacturer Part Number KA3403D Manufacturer ON Semiconductor Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 14-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 0.4 V/μs Gain Bandwidth Product 9kHz -3db Bandwidth 1MHz Current - Input Bias 30nA Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel 20mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOIC		
Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps	Manufacturer Part Number	KA3403D
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps 14-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 0.4 V/µs Gain Bandwidth Product -3db Bandwidth IMHz Current - Input Bias Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel 20mA Voltage - Supply, Single/Dual (±) Operating Temperature Mounting Type Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP	Manufacturer	ON Semiconductor
Package 14-SOIC (0.154", 3.90mm Width) Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 0.4 V/μs Gain Bandwidth Product 9kHz -3db Bandwidth 1MHz Current - Input Bias 30nA Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel 20mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP	Category	Integrated Circuits (ICs)
Series - Amplifier Type General Purpose Number of Circuits 4 Output Type - Slew Rate 0.4 V/μs Gain Bandwidth Product 9kHz -3db Bandwidth IMHz Current - Input Bias 30nA Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel 20mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type Number of Circuits 4 Output Type - Slew Rate 0.4 V/μs Gain Bandwidth Product -3db Bandwidth 1MHz Current - Input Bias 30nA Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	14-SOIC (0.154", 3.90mm Width)
Number of Circuits 4 Output Type - Slew Rate 0.4 V/ μ s Gain Bandwidth Product 9kHz -3db Bandwidth 1MHz Current - Input Bias 30nA Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel 20mA Voltage - Supply, Single/Dual (\pm) 3 V ~ 36 V, \pm 1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP	Series	-
Output Type Slew Rate 0.4 V/µs Gain Bandwidth Product 9kHz -3db Bandwidth 1MHz Current - Input Bias 30nA Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package	Amplifier Type	General Purpose
Slew Rate Gain Bandwidth Product -3db Bandwidth 1MHz Current - Input Bias Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Circuits	4
Gain Bandwidth Product -3db Bandwidth 1MHz Current - Input Bias 30nA Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel 20mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP	Output Type	-
-3db Bandwidth 1MHz Current - Input Bias 30nA Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel 20mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP	Slew Rate	0.4 V/µs
Current - Input Bias Voltage - Input Offset 1.5mV Current - Supply 2.3mA Current - Output / Channel 20mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package	Gain Bandwidth Product	9kHz
Voltage - Input Offset Current - Supply 2.3mA Current - Output / Channel 20mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package	-3db Bandwidth	1MHz
Current - Supply 2.3mA Current - Output / Channel 20mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP	Current - Input Bias	30nA
Current - Output / Channel 20mA Voltage - Supply, Single/Dual (±) 3 V ~ 36 V, ±1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP	Voltage - Input Offset	1.5mV
Voltage - Supply, Single/Dual (\pm) 3 V ~ 36 V, \pm 1.5 V ~ 18 V Operating Temperature 0°C ~ 70°C Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP	Current - Supply	2.3mA
Operating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case14-SOIC (0.154", 3.90mm Width)Supplier Device Package14-SOP	Current - Output / Channel	20mA
Mounting Type Surface Mount Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP	Voltage - Supply, Single/Dual (±)	3 V ~ 36 V, ±1.5 V ~ 18 V
Package / Case 14-SOIC (0.154", 3.90mm Width) Supplier Device Package 14-SOP	Operating Temperature	0°C ~ 70°C
Supplier Device Package 14-SOP	Mounting Type	Surface Mount
	Package / Case	14-SOIC (0.154", 3.90mm Width)
	Supplier Device Package	14-SOP
Report errors'		Report errors?

KA3403D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KA3403D Payment Methods





















KA3403D Shipping Methods













If you have any question about KA3403D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com