

KAC-3 Information

Heisener.com

Part Number KAC-3
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CYLINDRICAL

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KAC-3 Specifications

| Manufacturer Part NumberKAC-3ManufacturerEatonCategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesKACFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.875" L (14.30mm x 47.63mm) | • • • • • • • • • • • • • • • • • • • | |
|--|---------------------------------------|---|
| Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series KAC Fuse Type Cartridge Current Rating 3A Voltage Rating - AC 600V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Four Class - Class - Class - Class - Class Cylindrical, Blade Terminal (Bolt) Doerating Temperature Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension | Manufacturer Part Number | KAC-3 |
| Beckage Cylindrical, Blade Terminal (Bolt) Series KAC Fuse Type Cartridge Current Rating 3A Voltage Rating - AC 600V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.875" L (14.30mm x 47.63mm) | Manufacturer | Eaton |
| Package Cylindrical, Blade Terminal (Bolt) Series KAC Fuse Type Cartridge Current Rating 3A Voltage Rating - AC 600V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.875" L (14.30mm x 47.63mm) | Category | Circuit Protection |
| SeriesKACFuse TypeCartridgeCurrent Rating3AVoltage Rating - AC600VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.875" L (14.30mm x 47.63mm) | | Electrical, Specialty Fuses |
| Fuse Type Current Rating 3A Voltage Rating - AC 600V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge 600V - Eartridge Approval - But Approval Class - Cartridge - Bolt Mount Follow Cartridge Approval Coverating Capacity @ Rated Voltage Approvals Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge Approval Approval Culture Cartridge Approval App | Package | Cylindrical, Blade Terminal (Bolt) |
| Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3A 400000 40000 40000 40000 40000 40000 40000 40000 40000 400000 40000 40000 40000 40000 40000 40000 40000 40000 400000 40000 40000 40000 40000 40000 40000 40000 40000 400000 40000 40000 40000 40000 40000 40000 40000 40000 400000 40000 | Series | KAC |
| Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 600V 60 | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class - Class - Class - Class Cylindrical, Blade Terminal (Bolt) O.563" Dia x 1.875" L (14.30mm x 47.63mm) | Current Rating | 3A |
| Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class Class CuR Class Culk CuR Culk Culk Culk Culk Culk Culk Culk Culk | Voltage Rating - AC | 600V |
| Applications Electrical, Industrial Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.875" L (14.30mm x 47.63mm) | Voltage Rating - DC | - |
| Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.875" L (14.30mm x 47.63mm) | Response Time | - |
| Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.875" L (14.30mm x 47.63mm) | Applications | Electrical, Industrial |
| Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR | Features | - |
| Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.875" L (14.30mm x 47.63mm) | Class | - |
| Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.875" L (14.30mm x 47.63mm) | Approvals | UR |
| Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.875" L (14.30mm x 47.63mm) | Operating Temperature | - |
| Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.875" L (14.30mm x 47.63mm) | Breaking Capacity @ Rated Voltage | 200kA |
| Size / Dimension 0.563" Dia x 1.875" L (14.30mm x 47.63mm) | Mounting Type | Bolt Mount |
| | Package / Case | Cylindrical, Blade Terminal (Bolt) |
| Report errors? | Size / Dimension | 0.563" Dia x 1.875" L (14.30mm x 47.63mm) |
| | | Report errors? |

KAC-3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KAC-3 Payment Methods



















KAC-3 Shipping Methods













If you have any question about KAC-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com