

KAL100FB400R

KAL100FB400R Information

Contract service states there	 KAL100FB400R Stackpole Electronics Inc. Resistors Chassis Mount Resistors RES CHAS MNT 400 OHM 1% 100W Axial, Box For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



KAL100FB400R Specifications

Manufacturer Part Number KAL100FB400R Manufacturer Stackpole Electronics Inc. Category Resistors Chassis Mount Resistors Chassis Mount Resistors Package Axial, Box Series KAL Resistance 400 Ohms Tolerance ±1% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±20pm/°C Operating Temperature 55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature 5304" L x 2.756" W (89.00mm x 70.00mm) Height - Seated (Max) 1.791" (45.50mm) Lead Style Solder Lugs Package / Case Axial, Box		
CategoryResistorsChassis Mout ResistorsPackageAxial, BoxSeriesKALResistance400 OhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeFlangesSize / Dimension3.504" L x 2.756" W (89.00mm x 70.00mm)Height - Seated (Max)Solder LugsPackage / CaseAxial, BoxFalure RateSolder LugsFalure Rate-	Manufacturer Part Number	KAL100FB400R
Chassis Mount ResistorsPackageAxial, BoxSeriesKALResistance400 OhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.504" L x 2.756" W (89.00mm x 70.00mm)Height - Seated (Max)1.791" (45.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer	Stackpole Electronics Inc.
PackageAxial, BoxSeriesKALResistance400 OhmsTolerance±1%Power (Watts)100WCompositionWirewoundTomperature Coefficient±20pm/°COperating Temperature-55°C ~275°CFeaturesMoisture ResistantCoating, Housing TypeFlagesSize / Dimension5.04" L x 2.756" W (89.00mm x 70.00mm)Height - Seated (Max)1.791" (45.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFalure Rate-	Category	Resistors
SeriesKALResistance400 OhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±20pm/°COperating Temperature55°C ~ 275°CFeaturesMoisture ResistantCotaing, Housing TypeAluminumNounting Feature510°L × 275° W (89.00mm x 70.00mm)Size / Dimension3.504°L x 2.756° W (89.00mm x 70.00mm)Height - Seated (Max)1.791°(45.50mm)Lead StyleSolder LugsPackage / CaseAia, BoxFailure Rate-		Chassis Mount Resistors
Resistance400 OhmsTolerance±1%Power (Watts)100WCompositionWirewoundTemperature Coefficient±20pm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting Feature560″ L x 2.756″ W (89.00mm x 70.00mm)Size / Dimension.504″ L x 2.756″ W (89.00mm x 70.00mm)Height - Seated (Max).191″ (45.50mm)Lead StyleSolder LugsPackage / Case.Failure Rate.	Package	Axial, Box
Tolerance±1%Tolerance±1%Power (Watts)100WCompositionWirewoundComposition±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting Feature510°L ~ 275° W (89.00mm x 70.00mm)Size / Dimension1.091" (45.00mm)Height - Seated (Max)Solder LugsLead StyleSolder LugsPackage / CaseAxial, Box	Series	KAL
Power (Watts)Power (Watts)Power (Watts)100WCompositionWirewoundTemperature Coefficient±20pm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.504" L x 2.756" W (89.00mm x 70.00mm)Height - Seated (Max)1.791" (45.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Resistance	400 Ohms
CompositionWirewoundTemperature Coefficient $\pm 20ppm/^{C}$ COperating Temperature $-55^{\circ}C \sim 275^{\circ}C$ FeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $.554^{\circ}L x 2.756^{\circ}W (89.00mm x 70.00mm)$ Height - Seated (Max) $.191^{\circ}(45.50mm)$ Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate $-$	Tolerance	±1%
Temperature Coefficient±20pm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.504" L x 2.756" W (89.00mm x 70.00mm)Height - Seated (Max)1.791" (45.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Power (Watts)	100W
Operating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.504" L x 2.756" W (89.00mm x 70.00mm)Height - Seated (Max)1.791" (45.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Composition	Wirewound
FeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.504" L x 2.756" W (89.00mm x 70.00mm)Height - Seated (Max)1.791" (45.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Temperature Coefficient	±20ppm/°C
Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension3.504" L x 2.756" W (89.00mm x 70.00mm)Height - Seated (Max)1.791" (45.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Operating Temperature	-55°C ~ 275°C
Mounting FeatureFlangesSize / Dimension3.504" L x 2.756" W (89.00mm x 70.00mm)Height - Seated (Max)1.791" (45.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Features	Moisture Resistant
Size / Dimension 3.504" L x 2.756" W (89.00mm x 70.00mm) Height - Seated (Max) 1.791" (45.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)1.791" (45.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	3.504" L x 2.756" W (89.00mm x 70.00mm)
Package / CaseAxial, BoxFailure Rate-	Height - Seated (Max)	1.791" (45.50mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

KAL100FB400R Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

KAL100FB400R Payment Methods





If you have any question about KAL100FB400R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com