



KAL10JBR500 Information

Heisener.com

Part Number KAL10JBR500

Manufacturer Stackpole Electronics Inc.

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 0.5 OHM 5% 12.5W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KAL10JBR500 Specifications

Manufacturer Part NumberKAL10JBR500ManufacturerStackpole Electronics Inc.CategoryResistorsPackageAxial, BoxSeriesKALResistance500 mOhmsTolerance±5%Power (Watts)12.5WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)Height - Seated (Max)0.421" (10.70mm)		
Category Resistors Package Axial, Box Series KAL Resistance 500 mOhms Tolerance ±5% Power (Watts) 12.5W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Manufacturer Part Number	KAL10JBR500
PackageAxial, BoxSeriesKALResistance500 mOhmsTolerance±5%Power (Watts)12.5WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)	Manufacturer	Stackpole Electronics Inc.
PackageAxial, BoxSeriesKALResistance500 mOhmsTolerance±5%Power (Watts)12.5WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)	Category	Resistors
SeriesKALResistance500 mOhmsTolerance±5%Power (Watts)12.5WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)		Chassis Mount Resistors
Resistance500 mOhmsTolerance±5%Power (Watts)12.5WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.750" L x 0.800" W (19.05mm x 20.32mm)	Package	Axial, Box
Tolerance ±5% Power (Watts) 12.5W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Series	KAL
Power (Watts) 12.5W Composition Wirewound Temperature Coefficient $\pm 50 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 275^{\circ}\text{C}$ Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Resistance	500 mOhms
Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Tolerance	±5%
Temperature Coefficient ± 50 ppm/°C Operating Temperature -55 °C ~ 275 °C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750 " L x 0.800 " W $(19.05$ mm x 20.32 mm)	Power (Watts)	12.5W
Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Composition	Wirewound
Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Temperature Coefficient	±50ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Operating Temperature	-55°C ~ 275°C
Mounting Feature Flanges Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Features	Moisture Resistant
Size / Dimension 0.750" L x 0.800" W (19.05mm x 20.32mm)	Coating, Housing Type	Aluminum
· · · · · · · · · · · · · · · · · · ·	Mounting Feature	Flanges
Height - Seated (Max) 0.421" (10.70mm)	Size / Dimension	0.750" L x 0.800" W (19.05mm x 20.32mm)
	Height - Seated (Max)	0.421" (10.70mm)
Lead Style Solder Lugs	Lead Style	Solder Lugs
Package / Case Axial, Box	Package / Case	Axial, Box
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

KAL10JBR500 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KAL10JBR500 Payment Methods



















KAL10JBR500 Shipping Methods













If you have any question about KAL10JBR500, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com