



KAL25FB3R00 Information



For Reference Only

Part Number KAL25FB3R00

Manufacturer Stackpole Electronics Inc.

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 3 OHM 1% 25W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KAL25FB3R00 Specifications

Manufacturer Part NumberKAL25FB3R00ManufacturerStackpole Electronics Inc.CategoryResistorsPackageAxial, BoxSeriesKALResistance3 OhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.577" (14.66mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-Report errors?	•	
Resistors Chassis Mount Resistors Package Axial, Box Series KAL Resistance 3 Ohms Tolerance ±1% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate	Manufacturer Part Number	KAL25FB3R00
Chassis Mount Resistors Package Axial, Box KAL Resistance 3 Ohms Tolerance ±1% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate	Manufacturer	Stackpole Electronics Inc.
PackageAxial, BoxSeriesKALResistance3 OhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.577" (14.66mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesKALResistance3 OhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.577" (14.66mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance3 OhmsTolerance±1%Power (Watts)25WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.062" L x 1.080" W (26.97mm x 27.43mm)Height - Seated (Max)0.577" (14.66mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±1% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	KAL
Power (Watts) Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Resistance	3 Ohms
Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	$\pm 1\%$
Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	25W
Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm) Lead Style Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±50ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm) Lead Style Package / Case Axial, Box Failure Rate -	Operating Temperature	-55°C ~ 275°C
Mounting Feature Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm) Lead Style Package / Case Axial, Box Failure Rate -	Features	Moisture Resistant
Size / Dimension 1.062" L x 1.080" W (26.97mm x 27.43mm) Height - Seated (Max) 0.577" (14.66mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	1.062" L x 1.080" W (26.97mm x 27.43mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.577" (14.66mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

KAL25FB3R00 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KAL25FB3R00 Payment Methods



















KAL25FB3R00 Shipping Methods













If you have any question about KAL25FB3R00, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com