



KAL50FB1K20 Information

Part Number KAL50FB1K20

Manufacturer Stackpole Electronics Inc.

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1.2K OHM 1% 50W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KAL50FB1K20 Specifications

Manufacturer Part NumberKAL50FB1K20ManufacturerStackpole Electronics Inc.CategoryResistorsPackageAxial, BoxSeriesKALResistance1.2 kOhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±20pm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-Report errors?		
CategoryResistorsPackageAxial, BoxSeriesKALResistance1.2 kOhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	KAL50FB1K20
Chassis Mount Resistors Package Axial, Box KAL Resistance 1.2 kOhms Tolerance ±1% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate	Manufacturer	Stackpole Electronics Inc.
PackageAxial, BoxSeriesKALResistance1.2 kOhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesKALResistance1.2 kOhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance 1.2 kOhms Tolerance ±1% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.641" (16.28mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Package	Axial, Box
Tolerance ±1% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.641" (16.28mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	KAL
Power (Watts) 50W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.641" (16.28mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Resistance	1.2 kOhms
Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.641" (16.28mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±1%
Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.641" (16.28mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	50W
Operating Temperature -55°C ~ 275°C Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.641" (16.28mm) Lead Style Package / Case Axial, Box Failure Rate - -55°C ~ 275°C Moisture Resistant Aluminum Solder Lugs -55°C ~ 275°C Aluminum Solder Lugs Axial, Box -	Composition	Wirewound
Features Moisture Resistant Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.641" (16.28mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.641" (16.28mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-55°C ~ 275°C
Mounting Feature Flanges Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate Failure Rate	Features	Moisture Resistant
Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm) Height - Seated (Max) 0.641" (16.28mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	1.968" L x 1.140" W (49.99mm x 28.96mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.641" (16.28mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

KAL50FB1K20 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KAL50FB1K20 Payment Methods



















KAL50FB1K20 Shipping Methods













If you have any question about KAL50FB1K20, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com