

# KAL50FB20K0

#### **KAL50FB20K0** Information

Sectorer cong	Part Number Manufacturer Category Description Package	KAL50FB20K0 Stackpole Electronics Inc. Resistors Chassis Mount Resistors RES CHAS MNT 20K OHM 1% 50W Axial, Box For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **KAL50FB20K0** Specifications

Manufacturer   Stackpole Electronics Inc.     Category   Resistors     Chassis Mount Resistors   Chassis Mount Resistors     Package   Axial, Box     Series   KAL     Resistance   20 kOhms     Tolerance   ±1%     Power (Watts)   50W     Composition   Wirewound     Topprafure Coefficient   ±20ppm/°C     Operating Temperature   -55°C ~ 275°C     Features   Moisture Resistant     Coating, Housing Type   Aluminum     Mounting Feature   Flanges     Size / Dimension   .6641" (16.28mm)     Height - Seated (Max)   O.641" (16.28mm)     Package / Case   Xial, Box		
CategoryResistorsPackageAxial, BoxPackageAxial, BoxSeriesKALResistance20 kOhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting Feature1.968" L x 1.140" W (49.99mm x 28.96mm)Bight - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	KAL50FB20K0
Chassis Mount ResistorsPackageAxial, BoxSeriesKALResistance20 kOhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.641" (16.28mm)Height - Seated (Max)Solder LugsPackage / CaseAxial, BoxFalure Rate-	Manufacturer	Stackpole Electronics Inc.
PackageAxial, BoxSeriesKALResistance20 kOhmsTolerance±1%Power (Wats)50WCompositionWirewoundTemperature Coefficient±20ppm°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeHuminumMounting Feature1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesKALResistance20 kOhmsTolerance±1%Power (Wats)50WCompositionWirewoundTemperature Coefficient±20pm/°COperating Temperature55°C ~ 275°CFeaturesMoisture ResistantCotaing, Housing TypeFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSider LugsParkage / CaseAinal BaxFailure Rate-		Chassis Mount Resistors
Resistance20 kOhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±20pm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting Feature1968" L x 1.140" W (49.99mm x 28.96mm)Size / Dimension0.641" (16.28mm)Height - Seated (Max)Solder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance±1%Power (Wats)50WCompositionWirewoundTemperature Coefficient±20pm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlagesSize / Dimension0.641° (16.28mm)Height - Seated (Max)Solder LugsPackage / CaseAxial, Box	Series	KAL
Power (Watts)S0WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Resistance	20 kOhms
CompositionWirewoundTemperature Coefficient $\pm 20ppm^{\circ}C$ Operating Temperature $-55^{\circ}C \sim 275^{\circ}C$ FeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension $-641^{\circ}$ (16.28mm)Height - Seated (Max)Solder LugsLead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate $-$	Tolerance	$\pm 1\%$
Temperature Coefficient±20pm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Power (Watts)	50W
Operating Temperature-55°C ~ 275°CFeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Composition	Wirewound
FeaturesMoisture ResistantCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Temperature Coefficient	±20ppm/°C
Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Operating Temperature	-55°C ~ 275°C
Mounting FeatureFlangesSize / Dimension1.968" L x 1.140" W (49.99mm x 28.96mm)Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Features	Moisture Resistant
Size / Dimension 1.968" L x 1.140" W (49.99mm x 28.96mm)   Height - Seated (Max) 0.641" (16.28mm)   Lead Style Solder Lugs   Package / Case Axial, Box   Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)0.641" (16.28mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	1.968" L x 1.140" W (49.99mm x 28.96mm)
Package / CaseAxial, BoxFailure Rate-	Height - Seated (Max)	0.641" (16.28mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

#### **KAL50FB20K0** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE SUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# KAL50FB20K0 Payment Methods





If you have any question about KAL50FB20K0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com