

KB-17AG-120 Information



For Reference Only

Part Number KB-17AG-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 10A 120V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KB-17AG-120 Specifications

Manufacturer Part NumberKB-17AG-120ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKBRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage120VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKBRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage120VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug	Manufacturer Part Number	KB-17AG-120
Package-SeriesKBRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage120VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KB Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 44mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 120VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug	Category	Relays
SeriesKBRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage120VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 44mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 120VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug	Package	-
Coil TypeLatching, Dual CoilCoil Current44mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage120VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug	Series	KB
Coil Current44mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage120VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug	Relay Type	General Purpose
Coil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)10ASwitching Voltage120VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug	Coil Type	Latching, Dual Coil
Contact Form 4PDT (4 Form C) Contact Rating (Current) 10A Switching Voltage 120VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug	Coil Current	44mA
Contact Rating (Current) Switching Voltage 120VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style 10A 120VAC - Max 102 VAC - Contact Rating (Current) 10A 120VAC - Max 102 VAC - Contact Rating (Current) 10A 120VAC - Max 102 VAC - Contact Rating (Current) 120VAC - Max 102 VAC - Contact Rating (Current) 120VAC - Max 102 VAC - Contact Rating (Current) 120VAC - Max 120VAC	Coil Voltage	120VAC
Switching Voltage 120VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) Operate Time Release Time - Retures Mounting Type Chassis Mount Termination Style 102 VAC 102 VAC 103 VAC 104 VAC 105 VAC 106 Voltage (Min) - Chassis Mount Solder Lug	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time Release Time - Features Mounting Type Chassis Mount Termination Style Solder Lug	Switching Voltage	120VAC - Max
Operate Time	Turn On Voltage (Max)	102 VAC
Release Time	Turn Off Voltage (Min)	-
Features - Chassis Mount Termination Style Solder Lug	Operate Time	-
Mounting Type Chassis Mount Termination Style Solder Lug	Release Time	-
Termination Style Solder Lug	Features	-
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Solder Lug
		Report errors?

KB-17AG-120 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KB-17AG-120 Payment Methods



















KB-17AG-120 Shipping Methods













If you have any question about KB-17AG-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com