



KHAU-17A12-12 Information



For Reference Only

Part Number KHAU-17A12-12

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 5A 12V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KHAU-17A12-12 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Potter & Brumfield Relays Relays Power Relays, Over 2 Amps Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 100mA Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) Turn On Voltage (Max)
Category Relays Power Relays, Over 2 Amps Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 100mA Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 10.2 VAC
Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 100mA Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage (Max) 10.2 VAC
Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 100mA Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 10.2 VAC
SeriesKHARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current100mACoil Voltage12VACContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)10.2 VAC
Relay Type General Purpose Coil Type Non Latching Coil Current 100mA Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 10.2 VAC
Coil TypeNon LatchingCoil Current100mACoil Voltage12VACContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)10.2 VAC
Coil Current 100mA Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 10.2 VAC
Coil Voltage 12VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 10.2 VAC
Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 10.2 VAC
Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 10.2 VAC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 10.2 VAC
Turn On Voltage (Max) 10.2 VAC
T OSSU I OS
Turn Off Voltage (Min)
Operate Time 13ms
Release Time 6ms
Features Insulation - Class B
Mounting Type Socketable
Termination Style Plug In
Report errors?

KHAU-17A12-12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KHAU-17A12-12 Payment Methods



















KHAU-17A12-12 Shipping Methods













If you have any question about KHAU-17A12-12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com