

KHAU-17A12-240 Information



For Reference Only

Part Number KHAU-17A12-240

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 5A 240V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KHAU-17A12-240 Specifications

Manufacturer Part Number KHAU-17A12-240 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 6mA Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKHARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)204 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	KHAU-17A12-240
Package-SeriesKHARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)204 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 6mA Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesKHARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6mACoil Voltage240 VACContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240 VAC - MaxTurn On Voltage (Max)204 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 6mA Coil Voltage 240VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current6mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)204 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Series	KHA
Coil Current6mACoil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)204 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage240VACContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)204 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Coil Current	6mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Coil Voltage	240VAC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 204 VAC Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Switching Voltage	240VAC - Max
Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	204 VAC
Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Operate Time	13ms
Mounting Type Socketable Termination Style Plug In	Release Time	6ms
Termination Style Plug In	Features	Insulation - Class B
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
· · · · · · · · · · · · · · · · · · ·		Report errors?

KHAU-17A12-240 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KHAU-17A12-240 Payment Methods

































If you have any question about KHAU-17A12-240, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com