



KHAU-17D12-12 Information



For Reference Only

Part Number KHAU-17D12-12

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 5A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KHAU-17D12-12 Specifications

Manufacturer Part Number KHAU-17D12-12 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In		
Category Relays Power Relays, Over 2 Amps Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Manufacturer Part Number	KHAU-17D12-12
Package-SeriesKHARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesKHARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 75mA Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Series	KHA
Coil Current75mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Coil Current	75mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Coil Voltage	12VDC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 7	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Switching Voltage	240VAC - Max
Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	9 VDC
Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Operate Time	13ms
Mounting Type Socketable Termination Style Plug In	Release Time	6ms
Termination Style Plug In	Features	Insulation - Class B
	Mounting Type	Socketable
Papart arrows?	Termination Style	Plug In
Report errors?		Report errors?

KHAU-17D12-12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KHAU-17D12-12 Payment Methods



















KHAU-17D12-12 Shipping Methods













If you have any question about KHAU-17D12-12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com