



KHAU-17D12-48 Information



For Reference Only

Part Number KHAU-17D12-48

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 5A 48V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KHAU-17D12-48 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Potter & Brumfield Relays Relays Power Relays, Over 2 Amps Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 18.75mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 140VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms		
Category Relays Power Relays, Over 2 Amps Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 18.75mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms	Manufacturer Part Number	KHAU-17D12-48
Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 18.75mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 18.75mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) Operate Time 13ms	Category	Relays
Series KHA Relay Type General Purpose Coil Type Non Latching Coil Current 18.75mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 18.75mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms	Package	-
Coil Type Non Latching Coil Current 18.75mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms	Series	KHA
Coil Current 18.75mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms	Coil Current	18.75mA
Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms	Coil Voltage	48VDC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) - Operate Time 13ms	Contact Rating (Current)	5A
Turn Off Voltage (Min) - Operate Time 13ms	Switching Voltage	240VAC - Max
Operate Time 13ms	Turn On Voltage (Max)	36 VDC
•	Turn Off Voltage (Min)	-
Release Time 6ms	Operate Time	13ms
Network Time	Release Time	6ms
Features Insulation - Class B	Features	Insulation - Class B
Mounting Type Socketable	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

KHAU-17D12-48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KHAU-17D12-48 Payment Methods



















KHAU-17D12-48 Shipping Methods













If you have any question about KHAU-17D12-48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com