

KHEA480F-48

KHEA480F-48 Information

	Part Number Manufacturer Category	KHEA480F-48 Cosel USA, Inc. Power Supplies - External/Internal (Off-Board)	
www.heisener.com	Description Package	AC DC Converters DIN RAIL POWER SUPPLIES 480W 85- - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



KHEA480F-48 Specifications

ManufacturerCosel USA, Inc.CategoryPower Supplies - External/Internal (Off-Board) AC DC ConvertersPackage-SeriesKHEASpriesKHEANumber of OutputsIncosedVoltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 6-Voltage - Output 7-Voltage - Output 7-Voltage - Solation-Voltage - Isolation-Voltage - Isolation- <th>•</th> <th></th> <th></th>	•				
CategoryPower Supplies - External/Internal (Off-Board) AC DC ConvertersPackage-SeriesKHEASpresKHEATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5480WPower (Watts)480WApplicationsITE (commercial)Voltage - Isolation3kV (3000V)Efficiency94%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Manufacturer Part Number	KHEA480F-48			
AC DC Converters Package - Series KHEA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation 10A Power (Watts) 480W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Universal Input Mounting Type DIN Rail Size / Dimension 4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Manufacturer	Cosel USA, Inc.			
Package-SeriesKHEATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 7-Voltage - Output 7-Voltage - Output 7-Voltage - Soltage-Voltage - Soltage- <t< td=""><td>Category</td><td colspan="4">Power Supplies - External/Internal (Off-Board)</td></t<>	Category	Power Supplies - External/Internal (Off-Board)			
SeriesKHEATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Ourrent - Output (Max)10APower (Watts)480WVoltage - Isolation3kV (3000V)Efficiency94%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeJN RailSiz / Dimension4,77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)		AC DC Converters			
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 - Voltage - Output 5 - Voltage - Solation ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Universal Input Mounting Type DIN Rai Size / Dimension 4.7" "L x 2.76" W x 4.88" H (1	Package	-			
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 10A Power (Wats) 480W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Universal Input Mounting Type DIN Rail Size / Dimension 4.77" L x 2.76" W x 4.88" H (121.2m x 70.0mm x 124.0mm)	Series	KHEA			
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 480W Applications TTE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Universal Input Mounting Type DIN Rail Size / Dimension 4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Туре	Enclosed			
Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 480W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Universal Input Mounting Type UN Rail Size / Dimension 4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Number of Outputs	1			
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 480W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, Remote On/Off, Universal Input Mounting Type DIN Rail Size / Dimension 4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Voltage - Input	85 ~ 264 VAC			
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)10APower (Watts)480WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency94%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Voltage - Output 1	48V			
Voltage - Output 4-Current - Output (Max)10APower (Watts)480WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency94%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Voltage - Output 2	-			
Current - Output (Max)10APower (Watts)480WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency94%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Voltage - Output 3	-			
Power (Watts)480WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency94%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Voltage - Output 4	-			
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency94%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Current - Output (Max)	10A			
Voltage - Isolation3kV (3000V)Efficiency94%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Power (Watts)	480W			
Efficiency94%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Applications	ITE (Commercial)			
Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Voltage - Isolation	3kV (3000V)			
FeaturesAdjustable Output, DC Input Capable, Remote On/Off, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Efficiency	94%			
Mounting Type DIN Rail Size / Dimension 4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Operating Temperature	$-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)			
Size / Dimension 4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)	Features	Adjustable Output, DC Input Capable, Remote On/Off, Universal Input			
	Mounting Type	DIN Rail			
Report errors?	Size / Dimension	4.77" L x 2.76" W x 4.88" H (121.2mm x 70.0mm x 124.0mm)			
			Report errors?		

KHEA480F-48 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

KHEA480F-48 Payment Methods



KHEA480F-48 Shipping Methods



If you have any question about KHEA480F-48, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com