



### KHU-17A11H-120 Information



For Reference Only

Part Number KHU-17A11H-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 3A 120V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **KHU-17A11H-120 Specifications**

Manufacturer Part NumberKHU-17A11H-120ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPackage-SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesNeon Indicator, Test Button		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         KHU           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         11mA           Coil Voltage         120VAC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         3A           Switching Voltage         240VAC - Max           Turn On Voltage (Max)         102 VAC           Turn Off Voltage (Min)         -           Operate Time         13ms           Release Time         6ms           Features         Neon Indicator, Test Button	Manufacturer Part Number	KHU-17A11H-120
Package - Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Neon Indicator, Test Button	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Neon Indicator, Test Button	Category	Relays
SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesNeon Indicator, Test Button		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Neon Indicator, Test Button	Package	-
Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Neon Indicator, Test Button	Series	KHU
Coil Current Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Neon Indicator, Test Button	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Neon Indicator, Test Button	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 3A  Switching Voltage 240VAC - Max  Turn On Voltage (Max) 102 VAC  Turn Off Voltage (Min) -  Operate Time 13ms  Release Time 6ms  Features Neon Indicator, Test Button	Coil Current	11mA
Contact Rating (Current)  Switching Voltage  240VAC - Max  Turn On Voltage (Max)  102 VAC  Turn Off Voltage (Min)  Operate Time  13ms  Release Time  6ms  Features  Neon Indicator, Test Button	Coil Voltage	120VAC
Switching Voltage 240VAC - Max  Turn On Voltage (Max) 102 VAC  Turn Off Voltage (Min) -  Operate Time 13ms  Release Time 6ms  Features Neon Indicator, Test Button	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  13ms  Release Time  6ms  Features  Neon Indicator, Test Button	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Neon Indicator, Test Button	Switching Voltage	240VAC - Max
Operate Time13msRelease Time6msFeaturesNeon Indicator, Test Button	Turn On Voltage (Max)	102 VAC
Release Time 6ms Features Neon Indicator, Test Button	Turn Off Voltage (Min)	-
Features Neon Indicator, Test Button	Operate Time	13ms
	Release Time	6ms
	Features	Neon Indicator, Test Button
Mounting Type Socketable	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

#### KHU-17A11H-120 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### KHU-17A11H-120 Payment Methods



















## KHU-17A11H-120 Shipping Methods













If you have any question about KHU-17A11H-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com