

KHU-17A13-120 Information



For Reference Only

Part Number KHU-17A13-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE 4PDT 2A 120V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KHU-17A13-120 Specifications

Manufacturer Part Number KHU-17A13-120 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Signal Relays, Up to 2 Amps Package - Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPackage-SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	KHU-17A13-120
Package-SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In		Signal Relays, Up to 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 10mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current10mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Series	KHU
Coil Current10mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketableTermination StylePlug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Coil Current	10mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Coil Voltage	120VAC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Switching Voltage	240VAC - Max
Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	102 VAC
Release Time 6ms Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features Insulation - Class B Mounting Type Socketable Termination Style Plug In	Operate Time	13ms
Mounting Type Socketable Termination Style Plug In	Release Time	6ms
Termination Style Plug In	Features	Insulation - Class B
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

KHU-17A13-120 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KHU-17A13-120 Payment Methods



















KHU-17A13-120 Shipping Methods













If you have any question about KHU-17A13-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com