

KHU-17A18-120 Information



For Reference Only

Part Number KHU-17A18-120

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 3A 120V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KHU-17A18-120 Specifications

Manufacturer Part NumberKHU-17A18-120ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11mACoil Voltage120VACContact Form4PDT (4 Form C)Contact Rating (Current)3ASwitching Voltage240VAC - MaxTurn On Voltage (Max)102 VACTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting TypeSocketable		
Category Relays Power Relays, Over 2 Amps Package - Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B	Manufacturer Part Number	KHU-17A18-120
Package - Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B	Category	Relays
Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B	Package	-
Coil Type Non Latching Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B	Series	KHU
Coil Current 11mA Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 3A Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B	Coil Current	11mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B	Coil Voltage	120VAC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 102 VAC Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features Insulation - Class B	Switching Voltage	240VAC - Max
Operate Time13msRelease Time6msFeaturesInsulation - Class B	Turn On Voltage (Max)	102 VAC
Release Time 6ms Features Insulation - Class B	Turn Off Voltage (Min)	-
Features Insulation - Class B	Operate Time	13ms
	Release Time	6ms
Mounting Type Socketable	Features	Insulation - Class B
U 1.	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

KHU-17A18-120 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KHU-17A18-120 Payment Methods



















KHU-17A18-120 Shipping Methods













If you have any question about KHU-17A18-120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com