



KHU-17D12L-24 Information



For Reference Only

Part Number KHU-17D12L-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 5A 24V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KHU-17D12L-24 Specifications

Manufacturer Part NumberKHU-17D12L-24ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPackage-SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.5mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesLED IndicatorMounting TypeSocketable		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.5mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesLED IndicatorMounting TypeSocketable	Manufacturer Part Number	KHU-17D12L-24
Package - Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 37.5mA Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type Socketable	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series KHU Relay Type General Purpose Coil Type Non Latching Coil Current 37.5mA Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type Socketable	Category	Relays
SeriesKHURelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.5mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesLED IndicatorMounting TypeSocketable		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 37.5mA Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type Socketable	Package	-
Coil TypeNon LatchingCoil Current37.5mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)5ASwitching Voltage240VAC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesLED IndicatorMounting TypeSocketable	Series	KHU
Coil Current 37.5mA Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type Socketable	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type Socketable	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 5A Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type Socketable	Coil Current	37.5mA
Contact Rating (Current) Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type 5A 240VAC - Max 18 VDC	Coil Voltage	24VDC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type Socketable	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type Socketable	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type Socketable	Switching Voltage	240VAC - Max
Operate Time 13ms Release Time 6ms Features LED Indicator Mounting Type Socketable	Turn On Voltage (Max)	18 VDC
Release Time 6ms Features LED Indicator Mounting Type Socketable	Turn Off Voltage (Min)	-
Features LED Indicator Mounting Type Socketable	Operate Time	13ms
Mounting Type Socketable	Release Time	6ms
	Features	LED Indicator
	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

KHU-17D12L-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KHU-17D12L-24 Payment Methods



















KHU-17D12L-24 Shipping Methods













If you have any question about KHU-17D12L-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com