



### KHX-17D11-24 Information

Heisener.com

Part Number KHX-17D11-24

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

RELAY GENERAL PURPOSE 4PDT 24V **Description** 

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **KHX-17D11-24 Specifications**

Manufacturer Part NumberKHX-17D11-24ManufacturerTE Connectivity Potter & Brumfield RelaysCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKHXRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.5mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting Type-Termination Style-		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesKHXRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.5mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting Type-Termination Style-	Manufacturer Part Number	KHX-17D11-24
Package - Series KHX Relay Type General Purpose Coil Type Non Latching Coil Current 37.5mA Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) - Switching Voltage - Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type - Termination Style -	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         KHX           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         37.5mA           Coil Voltage         24VDC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         -           Switching Voltage         -           Turn On Voltage (Max)         18 VDC           Turn Off Voltage (Min)         -           Operate Time         13ms           Release Time         6ms           Features         Insulation - Class B           Mounting Type         -           Termination Style         -	Category	Relays
SeriesKHXRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.5mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting Type-Termination Style-		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current37.5mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting Type-Termination Style-	Package	-
Coil TypeNon LatchingCoil Current37.5mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting Type-Termination Style-	Series	KHX
Coil Current37.5mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)-Switching Voltage-Turn On Voltage (Max)18 VDCTurn Off Voltage (Min)-Operate Time13msRelease Time6msFeaturesInsulation - Class BMounting Type-Termination Style-	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) - Switching Voltage - Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) - Operate Time 13ms Release Time 6ms Features Insulation - Class B Mounting Type - Termination Style -	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current)  Switching Voltage  - Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  13ms  Release Time  6ms  Features  Insulation - Class B  Mounting Type  - Termination Style	Coil Current	37.5mA
Contact Rating (Current)  Switching Voltage  - Turn On Voltage (Max)  18 VDC  Turn Off Voltage (Min)  Operate Time  13ms  Release Time  6ms  Features  Insulation - Class B  Mounting Type  - Termination Style	Coil Voltage	24VDC
Switching Voltage - Turn On Voltage (Max) 18 VDC  Turn Off Voltage (Min) - Operate Time 13ms  Release Time 6ms  Features Insulation - Class B  Mounting Type - Termination Style - Omega	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  13ms  Release Time  6ms  Features  Insulation - Class B  Mounting Type  - Termination Style  18 VDC  -  Insulation - Class B  -  Termination Style	Contact Rating (Current)	-
Turn Off Voltage (Min)  Operate Time  13ms  Release Time  6ms  Features  Insulation - Class B  Mounting Type  - Termination Style  -	Switching Voltage	-
Operate Time 13ms  Release Time 6ms  Features Insulation - Class B  Mounting Type -  Termination Style -	Turn On Voltage (Max)	18 VDC
Release Time 6ms Features Insulation - Class B Mounting Type - Termination Style -	Turn Off Voltage (Min)	-
Features Insulation - Class B  Mounting Type - Termination Style -	Operate Time	13ms
Mounting Type - Termination Style -	Release Time	6ms
Termination Style -	Features	Insulation - Class B
·	Mounting Type	-
Report errors?	Termination Style	-
		Report errors?

#### KHX-17D11-24 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# KHX-17D11-24 Payment Methods


































If you have any question about KHX-17D11-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com