



KLDR.125T Information



For Reference Only

Part Number KLDR.125T
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 125MA 600VAC/300VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLDR.125T Specifications

| Manufacturer Part Number KLDR.125T Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series POWR-GARD? KLDR Fuse Type Cartridge Current Rating 125mA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | | |
|--|-----------------------------------|---|
| Category Circuit Protection Electrical, Specialty Fuses Package 5 AG, 10mm x 38.1mm Series POWR-GARD? KLDR Fuse Type Cartridge Current Rating 125mA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5 AG, 10mm x 38.1mm Size / Dimension Circuit Protection Electrical, Specialty Fuses 5 AG, 10mm x 38.1mm Size / Dimension Circuit Protection Captridge Captridge Captridge Captridge CC, CSA, UL CO CC, CSA, UL CO Mounting Type Holder Package / Case 5 AG, 10mm x 38.1mm Size / Dimension O.406" Dia x 1.500" L (10.30mm x 38.10mm) | Manufacturer Part Number | KLDR.125T |
| Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series POWR-GARD? KLDR Fuse Type Cartridge Current Rating 125mA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage COKA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Manufacturer | Littelfuse Inc. |
| Package5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating125mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Category | Circuit Protection |
| SeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating125mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm) | | Electrical, Specialty Fuses |
| Fuse TypeCartridgeCurrent Rating125mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Package | 5AG, 10mm x 38.1mm |
| Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 125mA 600V 600V | Series | POWR-GARD? KLDR |
| Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 6 | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V 300V Approvals CC CC Approvals CC Approvals CE, CSA, UL - Breaking Capacity @ Rated Voltage AC, 20kA DC Holder 5AG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Current Rating | 125mA |
| Response Time Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Slow Transformer Protection CC Approvals - CC Holder Holder 5AG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Voltage Rating - AC | 600V |
| Applications Features - Class CC Approvals Ce, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Transformer Protection Transformer Protection Transformer Protection Transformer Protection Transformer Protection Holder CC Approvals CE, CSA, UL - Holder - Holder Fackage / Case SAG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Voltage Rating - DC | 300V |
| Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Response Time | Slow |
| Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension O.406" Dia x 1.500" L (10.30mm x 38.10mm) | Applications | Transformer Protection |
| Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Features | - |
| Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Class | CC |
| Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Approvals | CE, CSA, UL |
| Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Operating Temperature | - |
| Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Breaking Capacity @ Rated Voltage | 200kA AC, 20kA DC |
| Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) | Mounting Type | Holder |
| | Package / Case | 5AG, 10mm x 38.1mm |
| Report errors? | Size / Dimension | 0.406" Dia x 1.500" L (10.30mm x 38.10mm) |
| | | Report errors? |

KLDR.125T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLDR.125T Payment Methods





















KLDR.125T Shipping Methods













If you have any question about KLDR.125T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com