



KLDR.187HXP Information

Heisener.com

Part Number KLDR.187HXP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 187MA 600VAC/300VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLDR.187HXP Specifications

Manufacturer Part NumberKLDR.187HXPManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating187mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating187mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer Part Number	KLDR.187HXP
Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series POWR-GARD? KLDR Fuse Type Cartridge Current Rating 187mA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage COKA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating187mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating187mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating187mAVoltage Rating - AC600 VVoltage Rating - DC300 VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 187mA 600V 600V	Series	POWR-GARD? KLDR
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V 300V Approvals CC CC Approvals CC Approvals CE, CSA, UL - Breaking Capacity @ Rated Voltage AC, 20kA DC Holder 5AG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Current Rating	187mA
Response Time Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Slow Transformer Protection CC Approvals - CC Holder Holder 5AG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - AC	600V
Applications Features - Class CC Approvals Ce, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Transformer Protection Transformer Protection Transformer Protection Transformer Protection Transformer Protection Holder CC Approvals CE, CSA, UL - Holder - Holder Fackage / Case SAG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - DC	300V
Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Response Time	Slow
Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension O.406" Dia x 1.500" L (10.30mm x 38.10mm)	Applications	Transformer Protection
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Class	CC
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
	Size / Dimension	0.406" Dia x 1.500" L (10.30mm x 38.10mm)
Report errors?		Report errors?

KLDR.187HXP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLDR.187HXP Payment Methods



















KLDR.187HXP Shipping Methods













If you have any question about KLDR.187HXP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com