



### **KLDR008.T Information**



For Reference Only

Part Number KLDR008.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 8A 600VAC/300VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **KLDR008.T Specifications**

Manufacturer Part NumberKLDR008.TManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)Report errors?		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  5 AG, 10mm x 38.1mm  Series  POWR-GARD? KLDR  Fuse Type  Cartridge  Current Rating  8 A  Voltage Rating - AC  Voltage Rating - DC  8 Slow  Applications  Transformer Protection  Features  - Class  CC  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  5 AG, 10mm x 38.1mm  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  5 AG, 10mm x 38.1mm  Electrical, Specialty Fuses  5 AG, 10mm x 38.1mm  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  5 AG, 10mm x 38.1mm  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  5 AG, 10mm x 38.1mm  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  5 AG, 10mm x 38.10mm)	Manufacturer Part Number	KLDR008.T
Electrical, Specialty Fuses  Package 5AG, 10mm x 38.1mm  Series POWR-GARD? KLDR  Fuse Type Cartridge  Current Rating 8A  Voltage Rating - AC 600V  Voltage Rating - DC 300V  Response Time Slow  Applications Transformer Protection  Features - Class CC  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage COKA AC, 20kA DC  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600 VVoltage Rating - DC300 VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating  Voltage Rating - AC  600V  Voltage Rating - DC  300V  Response Time  Slow  Applications  Transformer Protection  Features  - Class  CC  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  8A  8A  8A  600V  600V	Series	POWR-GARD? KLDR
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Slow  Applications  Transformer Protection  Features  - Class  CC  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  6	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Transformer Protection  Features  - Class  CC  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  300V  300V  300V  300V  300V  Approvals  CC  CC  Approvals  CC  Approvals  CE, CSA, UL  - Breaking Capacity @ Rated Voltage  AC, 20kA DC  Holder  5AG, 10mm x 38.1mm  0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Current Rating	8A
Response Time  Applications  Transformer Protection  Features  - Class  CC  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  Slow  Transformer Protection  CC  Approvals  - CC  Holder  Holder  5AG, 10mm x 38.1mm  0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - AC	600V
Applications Features - Class CC Approvals Ce, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Transformer Protection  Transformer Protection  Transformer Protection  Transformer Protection  Transformer Protection  Holder  CC  Approvals CE, CSA, UL  - Holder - Holder Fackage / Case SAG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - DC	300V
Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Response Time	Slow
Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension O.406" Dia x 1.500" L (10.30mm x 38.10mm)	Applications	Transformer Protection
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Class	CC
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.30mm x 38.10mm)
		Report errors?

### **KLDR008.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **KLDR008.T Payment Methods**


































If you have any question about KLDR008.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com