



KLDR008.TXP Information



For Reference Only

Part Number KLDR008.TXP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 8A 600VAC/300VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLDR008.TXP Specifications

Manufacturer Part Number KLDR008.TXP Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series POWR-GARD? KLDR Fuse Type Cartridge Current Rating 8A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm) Report errors?		
CategoryCircuit ProtectionElectrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer Part Number	KLDR008.TXP
Beaking Capacity @ Rated Voltage Electrical, Specialty Fuses Fluetrical, Specialty Fuses 5AG, 10mm x 38.1mm Electrical, Specialty Fuses 5AG, 10mm x 38.1mm 5Ize / Dimension Electrical, Specialty Fuses 5AG, 10mm x 38.1mm 5AG, 10mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLDRFuse TypeCartridgeCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsTransformer ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 8A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge 600V Cov Transformer Protection CC CC CC CC CC CC CC CC CSA, UL COPIC TURN COV CE, CSA, UL COV CE, CSA, UL COV	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 8A 8A 8A 600V 600	Series	POWR-GARD? KLDR
Voltage Rating - AC Voltage Rating - DC 300V Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V 300V Slow CR Slow CC CC Approved - CC APPROVED - SIDE Slow Transformer Protection - CC CC APPROVED - CC APPROVED - CE, CSA, UL - CE,	Current Rating	8A
Response Time Applications Transformer Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Slow Transformer Protection - CC Whom Protection - CC Approvals CE, CSA, UL - CE, CSA,	Voltage Rating - AC	600V
Applications Features - Class CC Approvals Ce, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case SAG, 10mm x 38.1mm Size / Dimension Transformer Protection CC Houndary Frankformer Protection CC Holder - CC Holder - CE, CSA, UL - C	Voltage Rating - DC	300V
Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Response Time	Slow
Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension O.406" Dia x 1.500" L (10.30mm x 38.10mm)	Applications	Transformer Protection
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Class	CC
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.30mm x 38.10mm)
		Report errors?

KLDR008.TXP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLDR008.TXP Payment Methods





















KLDR008.TXP Shipping Methods













If you have any question about KLDR008.TXP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com