

KLEA120F-48

KLEA120F-48 Information

www.Holsener.com	 KLEA120F-48 Cosel USA, Inc. Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC POWER SUPPLY, DIN RAIL - For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



KLEA120F-48 Specifications

ManufacturerCosel USA, Inc.Power Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesKLEATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 9-Voltage - Output 4-Current - Output (Max)2.5APower (Watts)ITE (Commercial)ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesMounting TypeMounting TypeDIN Rail	_			
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesKLEASpresEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 9-Voltage - Output 9-Voltage - Output 4-Current - Output (Max)2.5APower (Watts)120WApplicationsITE (Commercial)Voltage - Isolation3kV (300V)Efficiency88%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Manufacturer Part Number	KLEA120F-48		
AC DC Converters Package - Series KLEA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications TE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Manufacturer	Cosel USA, Inc.		
Package-SeriesKLEATypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Solation-Voltage - Isolation-Ster / Ore C - Ore C With Derating)Features-Mounting TypeDIN RailSize / Dimension4.71" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Category	Power Supplies - External/Internal (Off-Board)		
Series KLEA Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Wats) 120W Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.71" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)		AC DC Converters		
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Solation 2.5A Voltage - Isolation 120W Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.7" "L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Package	-		
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Series	KLEA		
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Туре	Enclosed		
Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency 88% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, PFC, Universal Input Mounting Type DIN Rail Size / Dimension 4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Number of Outputs	1		
Voltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.5APower (Watts)120WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3-Voltage - Output 4-Current - Output (Max)2.5APower (Watts)120WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Voltage - Output 1	48V		
Voltage - Output 4-Current - Output (Max)2.5APower (Watts)120WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Voltage - Output 2	-		
Current - Output (Max)2.5APower (Watts)120WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Voltage - Output 3	-		
Power (Watts)120WApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Voltage - Output 4	-		
ApplicationsITE (Commercial)Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Current - Output (Max)	2.5A		
Voltage - Isolation3kV (3000V)Efficiency88%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Power (Watts)	120W		
Efficiency88%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Applications	ITE (Commercial)		
Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Voltage - Isolation	3kV (3000V)		
FeaturesAdjustable Output, PFC, Universal InputMounting TypeDIN RailSize / Dimension4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Efficiency	88%		
Mounting Type DIN Rail Size / Dimension 4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Operating Temperature	$-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)		
Size / Dimension 4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)	Features	Adjustable Output, PFC, Universal Input		
	Mounting Type	DIN Rail		
Report errors?	Size / Dimension	4.77" L x 1.46" W x 4.88" H (121.2mm x 37.0mm x 124.0mm)		
			Report errors?	

KLEA120F-48 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

KLEA120F-48 Payment Methods



KLEA120F-48 Shipping Methods



If you have any question about KLEA120F-48, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com