



## **KLKD.100H Information**

Heisener.com

Part Number KLKD.100H

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 100MA 600VAC/VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KLKD.100H Specifications**

Manufacturer Part NumberKLKD.100HManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	KLKD.100H
Electrical, Specialty Fuses  Package Cartridge, Non-Standard  Series POWR-GARD? KLKD  Fuse Type Cartridge  Current Rating 100mA  Voltage Rating - AC 600V  Voltage Rating - DC 600V  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  100mA 100mA 600V 600V 600V 600V 600V 600V 600V 600	Series	POWR-GARD? KLKD
Voltage Rating - AC  Voltage Rating - DC  600V  Response Time  Fast  Applications  Solar (Photovoltaic)  Features  - Class  - Approvals  CE, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  600V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  600V  600V	Current Rating	100mA
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Solar (Photovoltaic) Features CE, UL CE, UL COPETATION OF SOLAR OF SO	Voltage Rating - AC	600V
Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	600V
Features - Class - CE, UL  Approvals CE, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast
Class - Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Solar (Photovoltaic)
Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  100kA AC, 50kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CE, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	100kA AC, 50kA DC
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

### **KLKD.100H Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **KLKD.100H Payment Methods**



















## **KLKD.100H Shipping Methods**













If you have any question about KLKD.100H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com