



## **KLKD005.T Information**



For Reference Only

Part Number KLKD005.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 5A 600VAC/DC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KLKD005.T Specifications**

Manufacturer Part NumberKLKD005.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, CSA, UL, VDEOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, CSA, UL, VDEOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	KLKD005.T
Electrical, Specialty Fuses  Package Cartridge, Non-Standard  Series POWR-GARD? KLKD  Fuse Type Cartridge  Current Rating 5A  Voltage Rating - AC 600V  Voltage Rating - DC 600V  Response Time Fast  Applications Solar (Photovoltaic)  Features -  Class -  Approvals CE, CSA, UL, VDE  Operating Temperature  Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, CSA, UL, VDEOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, CSA, UL, VDEOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating5AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, CSA, UL, VDEOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals Ce, CSA, UL, VDE Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  5A 600V CE, CSA COV	Series	POWR-GARD? KLKD
Voltage Rating - AC  Voltage Rating - DC  600V  Response Time  Fast  Applications  Solar (Photovoltaic)  Features  - Class  - Approvals  CE, CSA, UL, VDE  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, CSA, UL, VDE Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  600V  60	Current Rating	5A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Solar (Photovoltaic) Features CE, CSA, UL, VDE CE, CSA, UL, VDE CE, CSA, UL, VDE Operating Temperature - CE, CSA, UL, VDE CE, CSA, UL, VDE CE, CSA, UL, VDE Operating Temperature - CE, CSA, UL, VDE Operating Temperature - CE, CSA, UL, VDE Operating Temperature - CE, CSA, UL, VDE - CE, CSA, U	Voltage Rating - AC	600V
Applications Solar (Photovoltaic)  Features - Class - Approvals CE, CSA, UL, VDE Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	600V
Features - Class - CE, CSA, UL, VDE  Operating Temperature - CE, CSA, DC  Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast
Class - Approvals CE, CSA, UL, VDE Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Solar (Photovoltaic)
Approvals CE, CSA, UL, VDE Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  100kA AC, 50kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CE, CSA, UL, VDE
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	100kA AC, 50kA DC
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

#### **KLKD005.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **KLKD005.T Payment Methods**



















## **KLKD005.T Shipping Methods**













If you have any question about KLKD005.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com