



KLKD020.H Information

Heisener.com

For Reference Only

Part NumberKLKD020.HManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 20A 600VAC/VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLKD020.H Specifications

Manufacturer Part NumberKLKD020.HManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	KLKD020.H
Package Cartridge, Non-Standard Series POWR-GARD? KLKD Fuse Type Cartridge Current Rating 20A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Eartridge, Non-Standard Size / Dimension 100kA AC, 50m A C	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating20AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 20A 600V 6	Series	POWR-GARD? KLKD
Voltage Rating - AC Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 600V 600V 600V 600V 600V Fast Fast Color Fast Color Fast Color Fast Color Fast Color Fast Approvals CE, UL CE, UL Color Catrridge, Non-Standard Output Output	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 600V	Current Rating	20A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Solar (Photovoltaic) Fast Chyotocolomic CE, UL CE, UL COPRAGE	Voltage Rating - AC	600V
Applications Solar (Photovoltaic) Features - Class - Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Solar (Photovoltaic) - CHOUSE AND CONTROL OF CON	Voltage Rating - DC	600V
Features - Class - Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast
Class - Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Solar (Photovoltaic)
Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CE, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	100kA AC, 50kA DC
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

KLKD020.H Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLKD020.H Payment Methods



















KLKD020.H Shipping Methods













If you have any question about KLKD020.H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com