



# **KLKD030.HXR Information**

Heisener.com

Part NumberKLKD030.HXRManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 30A 600VAC/VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KLKD030.HXR Specifications**

Manufacturer Part Number         KLKD030.HXR           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         Cartridge, Non-Standard           Series         POWR-GARD? KLKD           Fuse Type         Cartridge           Current Rating         30A           Voltage Rating - AC         600V           Voltage Rating - DC         600V           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         100kA AC, 50kA DC           Mounting Type         Holder           Package / Case         Cartridge, Non-Standard           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	KLKD030.HXR
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLKDFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  30A 30A 30A 30A 600V 600V 600V 600V 600V 600V 600V 60	Series	POWR-GARD? KLKD
Voltage Rating - AC  Voltage Rating - DC  600V  Response Time  Fast  Applications  Solar (Photovoltaic)  Features  - Class  - Approvals  CE, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  600V  600V  600V  600V  600V  Fast  Fast  Color  Fast  Color  Fast  Color  Fast  Color  Fast  Color  Fast  Approvals  CE, UL  CE, UL  Color  Catrridge, Non-Standard  Output  Output	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  600V  600V	Current Rating	30A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Solar (Photovoltaic) Fast Chyotocolomic CE, UL CE, UL COPRATION CE, UL COPRATION CONTRACTOR C	Voltage Rating - AC	600V
Applications Solar (Photovoltaic) Features - Class - Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Solar (Photovoltaic) - CHOUSE AND CONTROL OF CON	Voltage Rating - DC	600V
Features - Class - Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast
Class - Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Solar (Photovoltaic)
Approvals CE, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  100kA AC, 50kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CE, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	100kA AC, 50kA DC
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

### **KLKD030.HXR Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **KLKD030.HXR Payment Methods**



















# **KLKD030.HXR Shipping Methods**













If you have any question about KLKD030.HXR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com