



## **KLKR.100TS Information**



For Reference Only

Part NumberKLKR.100TSManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 100MA 600VAC/300VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **KLKR.100TS Specifications**

Manufacturer Part NumberKLKR.100TSManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLKRFuse TypeCartridgeCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsMotor ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.409" Dia x 1.500" L (10.40mm x 38.10mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLKRFuse TypeCartridgeCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsMotor ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Manufacturer Part Number	KLKR.100TS
Electrical, Specialty Fuses  Package 5AG, 10mm x 38.1mm  Series POWR-GARD? KLKR  Fuse Type Cartridge  Current Rating 100mA  Voltage Rating - AC 600V  Voltage Rating - DC 300V  Response Time Fast  Applications Motor Protection  Features - Class CC  Approvals CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage C00kA AC, 20kA DC  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? KLKR           Fuse Type         Cartridge           Current Rating         100mA           Voltage Rating - AC         600V           Voltage Rating - DC         300V           Response Time         Fast           Applications         Motor Protection           Features         -           Class         CC           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA AC, 20kA DC           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLKRFuse TypeCartridgeCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsMotor ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.409" Dia x 1.500" L (10.40mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating100mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsMotor ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Motor Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 100mA 600V 600V 600V 600V 600V 600V 600V 600	Series	POWR-GARD? KLKR
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Fast  Applications  Motor Protection  Features  - Class  CC  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  6	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Motor Protection  Features - Class CC  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  300V  Ratel  Fast  CC  Mount Protection  - CC  CC  Approvals CE, CSA, UL  - CE, CSA, UL  - CE, CSA, UL  COPIE CON	Current Rating	100mA
Response Time Applications Motor Protection  Features - Class CC Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension  Fast Motor Protection  CC CC  CC  Approvals CE, CSA, UL  - Breaking Capacity @ Rated Voltage AC, 20kA DC  Holder  5AG, 10mm x 38.1mm  0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Voltage Rating - AC	600V
Applications Motor Protection  Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Voltage Rating - DC	300V
Features - Class CC Approvals CE, CSA, UL Operating Temperature - Ereaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Response Time	Fast
Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension O.409" Dia x 1.500" L (10.40mm x 38.10mm)	Applications	Motor Protection
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Class	CC
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.409" Dia x 1.500" L (10.40mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.409" Dia x 1.500" L (10.40mm x 38.10mm)
		Report errors?

### **KLKR.100TS Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **KLKR.100TS Payment Methods**



















## **KLKR.100TS Shipping Methods**













If you have any question about KLKR.100TS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com