



KLKR.125T Information



For Reference Only

Part NumberKLKR.125TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 125MA 600VAC/300VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLKR.125T Specifications

Manufacturer Part NumberKLKR.125TManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLKRFuse TypeCartridgeCurrent Rating125mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLKRFuse TypeCartridgeCurrent Rating125mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer Part Number	KLKR.125T
Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series POWR-GARD? KLKR Fuse Type Cartridge Current Rating 125mA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage COKA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package 5AG, 10mm x 38.1mm Series POWR-GARD? KLKR Fuse Type Cartridge Current Rating 125mA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLKRFuse TypeCartridgeCurrent Rating125mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating125mAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 125mA 600V 600V	Series	POWR-GARD? KLKR
Voltage Rating - AC Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 600V 6	Current Rating	125mA
Response Time Applications Electrical, Industrial Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Fast Electrical, Industrial - CC APPROVAL CC APPROVAL CE, CSA, UL - Breaking Capacity @ Rated Voltage AC, 20kA DC Holder Fast 1 CO CC CA CE, CSA, UL CE, CSA, UL CO CE, CSA, UL C	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - DC	300V
Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Response Time	Fast
Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension O.406" Dia x 1.500" L (10.30mm x 38.10mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Class	CC
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.30mm x 38.10mm)
_		Report errors?

KLKR.125T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLKR.125T Payment Methods



















KLKR.125T Shipping Methods













If you have any question about KLKR.125T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com