



## **KLKR03.5TS Information**



For Reference Only

Part Number KLKR03.5TS
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 3.5A 600VAC/300VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **KLKR03.5TS Specifications**

Manufacturer Part Number         KLKR03.5TS           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? KLKR           Fuse Type         Cartridge           Current Rating         3.5A           Voltage Rating - AC         600V           Voltage Rating - DC         300V           Response Time         Fast           Applications         Motor Protection           Features         -           Class         CC           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA AC, 20kA DC           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.30mm x 38.10mm)		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  5 AG, 10mm x 38.1mm  Series  POWR-GARD? KLKR  Fuse Type  Cartridge  Current Rating  3.5 A  Voltage Rating - AC  Voltage Rating - DC  8 ayov  Response Time  Fast  Applications  Motor Protection  Features  - Class  CC  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  5 AG, 10mm x 38.1mm  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  5 AG, 10mm x 38.1mm  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  5 AG, 10mm x 38.1mm  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  5 AG, 10mm x 38.1mm  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  5 AG, 10mm x 38.1mm  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Circuit Protection  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Circuit Protection  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Circuit Protection  Size / Dimension  Capacity Fuses  Size / Dimension  Circuit Protection  Size / Dimension  Circuit Protection  Size / Dimension  Circuit Protection  Capacity Fuses  Capacity F	Manufacturer Part Number	KLKR03.5TS
Electrical, Specialty Fuses  Package 5AG, 10mm x 38.1mm  Series POWR-GARD? KLKR  Fuse Type Cartridge  Current Rating 3.5A  Voltage Rating - AC 600V  Voltage Rating - DC 300V  Response Time Fast  Applications Motor Protection  Features - Class CC  Approvals CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage COKA AC, 20kA DC  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? KLKR           Fuse Type         Cartridge           Current Rating         3.5A           Voltage Rating - AC         600V           Voltage Rating - DC         300V           Response Time         Fast           Applications         Motor Protection           Features         -           Class         CC           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA AC, 20kA DC           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLKRFuse TypeCartridgeCurrent Rating3.5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsMotor ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating3.5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsMotor ProtectionFeatures-ClassCCApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Motor Protection Features - Class CC Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  3.5A 600V	Series	POWR-GARD? KLKR
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time Fast  Applications Motor Protection  Features - Class CC  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  600V  600V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Motor Protection  Features - Class CC  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  300V  Ratel  Fast  CC  Mount Protection  - CC  CC  Aproved  CC  Approvals CE, CSA, UL  - Breaking Capacity @ Rated Voltage AC, 20kA DC  Holder  5AG, 10mm x 38.1mm  0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Current Rating	3.5A
Response Time Applications Motor Protection  Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension  Fast Motor Protection  CC  Author CC  Approvals CE, CSA, UL  - Breaking Capacity @ Rated Voltage AC, 20kA DC  Holder  10.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - AC	600V
Applications Motor Protection  Features - Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Voltage Rating - DC	300V
Features - Class CC Approvals CE, CSA, UL Operating Temperature - Ereaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Response Time	Fast
Class CC Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Applications	Motor Protection
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Class	CC
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.406" Dia x 1.500" L (10.30mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.30mm x 38.10mm)
		Report errors?

#### **KLKR03.5TS Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **KLKR03.5TS Payment Methods**



















### **KLKR03.5TS Shipping Methods**













If you have any question about KLKR03.5TS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com