



### **KLLU1800X Information**

Heisener.com

For Reference Only

Part Number KLLU1800X
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 1.8KA 600VAC/300VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KLLU1800X Specifications**

Manufacturer Part Number  Manufacturer  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD? KLLU  Fuse Type  Cartridge  Current Rating  1.8kA  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  - Class  L  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Store Circuit Fuses  Circuit Protection  Electrical, Industrial  CE, CSA, UL  Operating Temperature  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? KLLUFuse TypeCartridgeCurrent Rating1.8kAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Manufacturer Part Number	KLLU1800X
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt)  Series POWR-GARD? KLLU  Fuse Type Cartridge  Current Rating 1.8kA  Voltage Rating - AC 600V  Voltage Rating - DC 300V  Response Time Slow  Applications Electrical, Industrial  Features - Class L  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage COKA AC, 20kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? KLLUFuse TypeCartridgeCurrent Rating1.8kAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Category	Circuit Protection
Series POWR-GARD? KLLU Fuse Type Cartridge Current Rating 1.8kA Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating1.8kAVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Size / Dimension Size / Sign Sign Sign Sign Sign Sign Sign Sign	Series	POWR-GARD? KLLU
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  600V  600V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Current Rating	1.8kA
Response Time  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Slow  Electrical, Industrial  - Bleatrical, Industrial  - CE, CSA, UL  CE, CSA, UL  - CE, CSA, UL	Voltage Rating - AC	600V
Applications Electrical, Industrial  Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Voltage Rating - DC	300V
Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Response Time	Slow
Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Class	L
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	3.500" Dia x 3.752" L (88.90mm x 95.30mm)
		Report errors?

### **KLLU1800X Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **KLLU1800X Payment Methods**



















### **KLLU1800X Shipping Methods**













If you have any question about KLLU1800X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com