

KLNR006.T

KLNR006.T Information

		Part Number	KLNR006.T
	() Heisener.com	Manufacturer	Littelfuse Inc.
		Category	Circuit Protection Electrical, Specialty Fuses
	A Construction	Description	FUSE CARTRIDGE 6A 250VAC/125VDC
		Package	Cartridge, Non-Standard
			For the pricing/inventory/lead time, please contact
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



KLNR006.T Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLNRFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200KA AC, 20KA DCManufacturesCartridge, Non-StandardPackage / CaseCartridge, Non-Standard		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLNRFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRKIApprovalsCE, CSA, ULOperating Temperature200KA AC, 20KA DCBreaking Capacity @ Rated Voltage200KA AC, 20KA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Manufacturer Part Number	KLNR006.T
Electrical, Specialty FusesPackageCartridge, Non-StandardPackagePOWR-GARD? KLNRSeriesPOWR-GARD? KLNRFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? KLNRFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLNRFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating6ACurrent Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialApplications-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Package	Cartridge, Non-Standard
Current Rating6ACurrent Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Series	POWR-GARD? KLNR
Voltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassKK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Fuse Type	Cartridge
Voltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Current Rating	6A
Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Voltage Rating - AC	250V
ApplicationsElectrical, IndustrialApplications-Features-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Voltage Rating - DC	125V
Features-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Response Time	Fast
ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Class	RK1
Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Operating Temperature	-
Package / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)
		Report errors?

KLNR006.T Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about KLNR006.T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com