



## **KLNR045.T Information**

Heisener.com

For Reference Only

Part Number KLNR045.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 45A 250VAC/125VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KLNR045.T Specifications**

Manufacturer Part NumberKLNR045.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLNRFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)Report errors?		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cartridge, Non-Standard  Series  POWR-GARD? KLNR  Fuse Type  Cartridge  Current Rating  45A  Voltage Rating - AC  Voltage Rating - DC  125V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  RK1  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Electrical, Industrial  CE, CSA, UL  Operating Temperature  - Class  RK1  Approvals  CE, CSA, UL  Operating Temperature  - Cartridge, Non-Standard  Size / Dimension  O.811" Dia x 3.000" L (20.60mm x 76.20mm)	Manufacturer Part Number	KLNR045.T
Electrical, Specialty Fuses  Package Cartridge, Non-Standard  Series POWR-GARD? KLNR  Fuse Type Cartridge  Current Rating 45A  Voltage Rating - AC 250V  Voltage Rating - DC 125V  Response Time Fast  Applications Electrical, Industrial  Features - Class RK1  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? KLNRFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLNRFuse TypeCartridgeCurrent Rating45AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating45AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V  Voltage Rating - DC 125V  Response Time Fast Applications Electrical, Industrial Features - Class RK1  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  45A 45A 45A 45A 45A 45A 45A 45A 45A 45	Series	POWR-GARD? KLNR
Voltage Rating - AC  Voltage Rating - DC  125V  Response Time Fast  Applications Electrical, Industrial  Features - Class RK1  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  250V  125V  125	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class RK1  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  125V  Rate  Fast Catridge, Non-Standard Size / Dimension  Electrical, Industrial  CE, CSA, UL  COLOR  CARTING ARC  CE, CSA, UL  COLOR  COL	Current Rating	45A
Response Time Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial Feature - CLe, CSA, UL CE,	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Voltage Rating - DC	125V
Features - Class RK1  Approvals CE, CSA, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Response Time	Fast
Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 3.000" L (20.60mm x 76.20mm)
		Report errors?

#### **KLNR045.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **KLNR045.T Payment Methods**



















### **KLNR045.T Shipping Methods**













If you have any question about KLNR045.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com