



KLPC1350X Information

Heisener.com

Part NumberKLPC1350XManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 1.35KA 600VAC/480DC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLPC1350X Specifications

Manufacturer Part NumberKLPC1350XManufacturerLittelfuse Inc.CategoryCircuit ProtectionFackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?, POWR-PRO? KLPCFuse TypeCartridgeCurrent Rating1.35kAVoltage Rating - AC600VVoltage Rating - DC480VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 300kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.000" Dia x 3.752" L (76.20mm x 95.30mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? KLPC Fuse Type Cartridge Current Rating 1.35kA Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical (Bolt) Size / Dimension Circuit Protection Electrical, Blade Terminal (Bolt) Size / Dimension Size / Dimension Size / Dimension	Manufacturer Part Number	KLPC1350X
Beckage Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? KLPC Fuse Type Cartridge Current Rating 1.35kA Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?, POWR-PRO? KLPCFuse TypeCartridgeCurrent Rating1.35kAVoltage Rating - AC600VVoltage Rating - DC480VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 300kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? KLPCFuse TypeCartridgeCurrent Rating1.35kAVoltage Rating - AC600VVoltage Rating - DC480VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 300kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.000" Dia x 3.752" L (76.20mm x 95.30mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating1.35kAVoltage Rating - AC600VVoltage Rating - DC480VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 300kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Sincy 1.35kA 600V 480V 480V Electrical, Industrial Electrical, Industrial CE, CSA, UL CE, CSA, UL CE, CSA, UL Operating Temperature CURNA AC, 300kA DC Bolt Mount CURNA AC, 300kA DC Size / Dimension Size / Dimension 1.35kA 600V 60	Series	POWR-GARD?, POWR-PRO? KLPC
Voltage Rating - AC Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 600V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 480V 480V 480V 480V 480V 480V 800 Bolt Moustrial CL CE, CSA, UL CE, CSA, UL CE, CSA, UL CYLINDRICAL CE, CSA, UL COPICAL COP	Current Rating	1.35kA
Response Time Applications Electrical, Industrial Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Electrical, Industrial CE, CSA, UL - Bolt Mount CE, CSA, UL - CE, CSA, UL - CURRATION OF THE PROPERTY OF THE PR	Voltage Rating - AC	600V
Applications Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Electrical Electrical Elec	Voltage Rating - DC	480V
Features - Class L Approvals CE, CSA, UL Operating Temperature - Seraking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Response Time	Slow
Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Class	L
Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Breaking Capacity @ Rated Voltage	200kA AC, 300kA DC
Size / Dimension 3.000" Dia x 3.752" L (76.20mm x 95.30mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	3.000" Dia x 3.752" L (76.20mm x 95.30mm)
Report circles.		Report errors?

KLPC1350X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLPC1350X Payment Methods



















KLPC1350X Shipping Methods













If you have any question about KLPC1350X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com