



KLPC300.X Information

Heisener.com

Part Number KLPC300.X
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 300A 600VAC/480VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLPC300.X Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? KLPC Fuse Type Cartridge Current Rating 300A Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Electrical, Industrial Features - CE, CSA, UR Operating Temperature Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? KLPC Fuse Type Cartridge Current Rating 300A Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial CE, CSA, UR Operating Temperature Bolt Mount CE, CSA, UR Colindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	KLPC300.X
Flectrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? KLPC Fuse Type Cartridge Current Rating 300A Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Blade Terminal (Bolt) Size / Dimension Electrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? KLPC Fuse Type Cartridge Current Rating 300A Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? KLPCFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC600VVoltage Rating - DC480VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 300kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension2.500" Dia x 3.752" L (63.50mm x 95.30mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 300A Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Canon Cartridge 300A Cartridge 300A CE, CSA CSOW Dia x 3.752" L (63.50mm x 95.30mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 300A 600V	Series	POWR-GARD?, POWR-PRO? KLPC
Voltage Rating - AC Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600V 480V 600V 480V 600V 480V 600V 480V 600V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 480V 480V 480V 480V 480V 480V 80W Slow Electrical, Industrial - CE, CSA, UR CE, CSA, UR CYE, CSA, UR CYE, CSA, UR CYE, CSA, UR CYE, CSA, UR CYURA	Current Rating	300A
Response Time Applications Electrical, Industrial Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Electrical, Industrial CE, CSA, UR - Bolt Mount CE, CSA, UR - CUlindrical, Blade Terminal (Bolt) 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Voltage Rating - AC	600V
Applications Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial CE, CSA, UR CE, CSA, UR - Bolt Mount - CURRITHER OF THE OF TH	Voltage Rating - DC	480V
Features - Class L Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Response Time	Slow
Class L Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CE, CSA, UR CUR CUR CUR CONNECTED	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Class	L
Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Breaking Capacity @ Rated Voltage	200kA AC, 300kA DC
Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.500" Dia x 3.752" L (63.50mm x 95.30mm)
report errors.		Report errors?

KLPC300.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLPC300.X Payment Methods





















KLPC300.X Shipping Methods













If you have any question about KLPC300.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com