



KLPC3500X Information

Heisener.com

Part Number KLPC3500X
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 3.5KA 600VAC/480VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLPC3500X Specifications

Manufacturer Part NumberKLPC3500XManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?, POWR-PRO? KLPCFuse TypeCartridgeCurrent Rating3.5kAVoltage Rating - AC600VVoltage Rating - DC480VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 300kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension5.752" Dia x 4.000" L (146.10mm x 101.60mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?, POWR-PRO? KLPCFuse TypeCartridgeCurrent Rating3.5kAVoltage Rating - AC600VVoltage Rating - DC480VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 300kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Manufacturer Part Number	KLPC3500X
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? KLPC Fuse Type Cartridge Current Rating 3.5kA Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) S.752" Dia x 4.000" L (146.10mm x 101.60mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?, POWR-PRO? KLPCFuse TypeCartridgeCurrent Rating3.5kAVoltage Rating - AC600VVoltage Rating - DC480VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 300kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Category	Circuit Protection
SeriesPOWR-GARD?, POWR-PRO? KLPCFuse TypeCartridgeCurrent Rating3.5kAVoltage Rating - AC600VVoltage Rating - DC480VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 300kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension5.752" Dia x 4.000" L (146.10mm x 101.60mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating3.5kAVoltage Rating - AC600VVoltage Rating - DC480VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 300kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Size / Dimension 3.5kA 3.5kA 3.5kA 3.5kA 600V 480V 480V 480V Electrical, Industrial - CE, CSA, UL CE, CSA, UL CY, CSA, UL CURRENT CAPACITY CONTROL	Series	POWR-GARD?, POWR-PRO? KLPC
Voltage Rating - AC Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 600V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 480V 480V 480V 480V 480V 480V Electrical, Industrial - CE, CSA, UL CE, CSA, UL CY, CSA, UL	Current Rating	3.5kA
Response Time Applications Electrical, Industrial Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Electrical, Industrial - Bolt Mount CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Size / Dimension Slow CE, CSA, UL C	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Voltage Rating - DC	480V
Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Response Time	Slow
Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Class	L
Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Breaking Capacity @ Rated Voltage	200kA AC, 300kA DC
Size / Dimension 5.752" Dia x 4.000" L (146.10mm x 101.60mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	5.752" Dia x 4.000" L (146.10mm x 101.60mm)
		Report errors?

KLPC3500X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLPC3500X Payment Methods



















KLPC3500X Shipping Methods













If you have any question about KLPC3500X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com