



### **KLPC600.X Information**

Heisener.com

Part Number KLPC600.X

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 600A 600VAC/480VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **KLPC600.X Specifications**

Manufacturer       KLPC600.X         Manufacturer       Littelfuse Inc.         Category       Circuit Protection         Electrical, Specialty Fuses         Package       Cylindrical, Blade Terminal (Bolt)         Series       POWR-GARD?, POWR-PRO? KLPC         Fuse Type       Cartridge         Current Rating       600A         Voltage Rating - AC       600V         Voltage Rating - DC       480V         Response Time       Slow         Applications       Electrical, Industrial         Features       -         Class       L         Approvals       CE, CSA, UR         Operating Temperature       -         Breaking Capacity @ Rated Voltage       200kA AC, 300kA DC         Mounting Type       Bolt Mount         Package / Case       Cylindrical, Blade Terminal (Bolt)         Size / Dimension       2.500" Dia x 3.752" L (63.50mm x 95.30mm)		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD?, POWR-PRO? KLPC  Fuse Type  Cartridge  Current Rating  600A  Voltage Rating - AC  600V  Voltage Rating - DC  480V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Electrical, Industrial  CE, CSA, UR  Operating Temperature  - Breaking Capacity @ Rated Voltage  CURSA AC, 300kA DC  Size / Dimension  CIRCUIT Protection  Electrical, Specialty Fuses  Electrical, Sold Polity Coltage  CURSA AC, 300kA DC  Bolt Mount  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Blade Terminal (Bolt)  Cylindrical, Blade Terminal (Bolt)	Manufacturer Part Number	KLPC600.X
Beckrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? KLPC  Fuse Type Cartridge Current Rating 600A Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminal (Bolt)  Series POWR-GARD?, POWR-PRO? KLPC  Fuse Type Cartridge  Current Rating 600A  Voltage Rating - AC 600V  Voltage Rating - DC 480V  Response Time Slow  Applications Electrical, Industrial  Features -  Class L  Approvals CE, CSA, UR  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Category	Circuit Protection
Series POWR-GARD?, POWR-PRO? KLPC Fuse Type Cartridge Current Rating 600A Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 600A Voltage Rating - AC 600V Voltage Rating - DC 480V Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Conversed Conversed Conversed Cartridge 600A 600A 600A 600V 600V 600V 600V 600V	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating  Voltage Rating - AC  600V  Voltage Rating - DC  480V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  600A  600V	Series	POWR-GARD?, POWR-PRO? KLPC
Voltage Rating - AC  Voltage Rating - DC  480V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  600V  480V  600V  480V  600V  480V  600V  600V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  L  Approvals  CE, CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  480V  480V  480V  480V  480V  480V  800  Bolt Moustrial  CL  CE, CSA, UR  CE, CSA, UR  CE, CSA, UR  CYLINDRICAL  CE, CSA, UR  COPICAL  CE, CSA, UR  COPICAL  CE, CSA, UR  COPICAL  CE, CSA, UR  CE, CSA, UR  COPICAL  CE, CSA, UR  CE, CSA, UR  COPICAL  CE, CSA, UR  COPICAL  CE, CSA, UR  COPICAL  CE, CSA, UR  COPICAL  CE, CSA, UR  COPICAL  CE, CSA, UR  CE, CSA, UR	Current Rating	600A
Response Time  Applications  Electrical, Industrial  Features  - Class  L  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Slow  Electrical, Industrial  CE, CSA, UR  -  Bolt Mount  Bolt Mount  CE, CSA, UR  -  CURSA, 300kA DC  Mounting Type  Bolt Mount  CURSA, 300kA DC  Bolt Mount  CURSA, 300kA DC  CURS	Voltage Rating - AC	600V
Applications Electrical, Industrial  Features - Class L Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Voltage Rating - DC	480V
Features - Class L Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Response Time	Slow
Class L Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 300kA DC  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Class	L
Breaking Capacity @ Rated Voltage 200kA AC, 300kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Approvals	CE, CSA, UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Breaking Capacity @ Rated Voltage	200kA AC, 300kA DC
Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	2.500" Dia x 3.752" L (63.50mm x 95.30mm)
		Report errors?

### **KLPC600.X Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **KLPC600.X Payment Methods**



















## **KLPC600.X Shipping Methods**













If you have any question about KLPC600.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com