



KLSR006.T Information

A Heisener com

Part Number KLSR006.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 6A 600VAC/250VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLSR006.T Specifications

Manufacturer Part NumberKLSR006.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionBecktrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? KLSRFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRKIApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? KLSR Fuse Type Cartridge Current Rating 6A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Industrial CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	KLSR006.T
Beckage Cartridge, Non-Standard Series POWR-GARD? KLSR Fuse Type Cartridge Current Rating 6A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension (0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? KLSRFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLSRFuse TypeCartridgeCurrent Rating6AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 5.000" L (20.60mm x 127.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 6A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Coov 600V Catrridge Catrridge CECVA COV COV COV Catrridge Catrridge Catrridge Catrridge Catrridge Catrridge Cov Catrridge Cov Catrridge Cov Catrridge Cov	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 6A 600V 600V 600V 600V 600V 600V 600V	Series	POWR-GARD? KLSR
Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 250V East Color Colo	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V East Sixt Sixt Sixt Sixt Sixt Sixt Sixt Six	Current Rating	6A
Response Time Applications Electrical, Industrial Features - Class RK1 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial CE, CSA, UL OCE, CSA, UL CE, CSA	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Industrial CE, CSA RK1 ARA CE, CSA, UL CE, CSA, UL	Voltage Rating - DC	250V
Features - Class RK1 Approvals CE, CSA, UL Operating Temperature - Country @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Response Time	Fast
Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UL - CRACK CSA, U	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.811" Dia x 5.000" L (20.60mm x 127.00mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 5.000" L (20.60mm x 127.00mm)
_		Report errors?

KLSR006.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLSR006.T Payment Methods





















KLSR006.T Shipping Methods













If you have any question about KLSR006.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com