



KLSR080.V Information

Manufa Catego Heisener.com

Part Number KLSR080.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 80A 600VAC/300VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLSR080.V Specifications

Manufacturer Part NumberKLSR080.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? KLSRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)			
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesPOWR-GARD? KLSRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Manufacturer Part Number	KLSR080.V	
Beckrical, Specialty Fuses Cylindrical, Blade Terminals Series POWR-GARD? KLSR Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminals Size / Dimension Lass Size / Dimension Electrical, Industrial Features CE, CSA, UL CO, CSA, U	Manufacturer	Littelfuse Inc.	
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? KLSRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Category	Circuit Protection	
SeriesPOWR-GARD? KLSRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)		Electrical, Specialty Fuses	
Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Package	Cylindrical, Blade Terminals	
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 800 800 600V 600V	Series	POWR-GARD? KLSR	
Voltage Rating - AC Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V	Fuse Type	Cartridge	
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V Rate Fast CE, CSA RK1 CE, CSA, UL CE, CSA, UL COLUMN	Current Rating	80A	
Response Time Applications Electrical, Industrial Features - Class RK1 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Electrical, Industrial - CE, CSA, UL - CE, C	Voltage Rating - AC	600V	
Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Voltage Rating - DC	300V	
Features - Class RK1 Approvals CE, CSA, UL Operating Temperature - Country @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Response Time	Fast	
Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Applications	Electrical, Industrial	
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension CE, CSA, UL CHARALLE CON CONTROL C	Features	-	
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Class	RK1	
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Approvals	CE, CSA, UL	
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Operating Temperature	-	
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC	
Size / Dimension 1.311" Dia x 7.874" L (33.30mm x 200.00mm)	Mounting Type	Holder	
· · · · · · · · · · · · · · · · · · ·	Package / Case	Cylindrical, Blade Terminals	
D ()	Size / Dimension	1.311" Dia x 7.874" L (33.30mm x 200.00mm)	
Report errors?		Re	port errors?

KLSR080.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLSR080.V Payment Methods

































If you have any question about KLSR080.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com