



KLSR450.X Information

Ma Car Heisener.com

Part NumberKLSR450.XManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 450A 600VAC/300VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLSR450.X Specifications

Manufacturer Part NumberKLSR450.XManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? KLSRFuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.094" Dia x 13.374" L (78.60mm x 339.70mm)Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? KLSRFuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Manufacturer Part Number	KLSR450.X
Electrical, Specialty Fuses Package Cylindrical, Blade Terminals Series POWR-GARD? KLSR Fuse Type Cartridge Current Rating 450A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminals Size / Dimension Electrical, Industrial Features - CLass RK1 APPROVALS CE, CSA, UL COPERATION CONTRACTOR CONT	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? KLSRFuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Category	Circuit Protection
Series POWR-GARD? KLSR Fuse Type Cartridge Current Rating 450A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating450AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassRK1ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Package	Cylindrical, Blade Terminals
Current Rating 450A Voltage Rating - AC 600V Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Series	POWR-GARD? KLSR
Voltage Rating - AC Voltage Rating - DC 300V Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 300V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V Rate Fast Class Fast Clectrical, Industrial - RK1 - RK1 - RK1 - CE, CSA, UL - CU, CSA, UL	Current Rating	450A
Response Time Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Fast Fast Fast Fast Fast Flast Flast Approvals - CUlsas RK1 Approvals CE, CSA, UL - CE, CSA,	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Voltage Rating - DC	300V
Features - Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Response Time	Fast
Class RK1 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Class	RK1
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 3.094" Dia x 13.374" L (78.60mm x 339.70mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	3.094" Dia x 13.374" L (78.60mm x 339.70mm)
		Report errors?

KLSR450.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLSR450.X Payment Methods





















KLSR450.X Shipping Methods













If you have any question about KLSR450.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com