

KLU-1600 Information

www.lsener.com

Part Number KLU-1600 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 1.6KA 600VAC CYL

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KLU-1600 Specifications

Manufacturer Part NumberKLU-1600ManufacturerEatonCategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesLimitron? KLUFuse TypeCartridgeCurrent Rating1.6kAVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.000" Dia x 3.750" L (76.20mm x 95.25mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series Limitron? KLU Fuse Type Cartridge Current Rating 1.6kA Voltage Rating - AC 600V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer Part Number	KLU-1600
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series Limitron? KLU Fuse Type Cartridge Current Rating 1.6kA Voltage Rating - AC 600V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Signature (Color of the color of th	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesLimitron? KLUFuse TypeCartridgeCurrent Rating1.6kAVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.000" Dia x 3.750" L (76.20mm x 95.25mm)	Category	Circuit Protection
SeriesLimitron? KLUFuse TypeCartridgeCurrent Rating1.6kAVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassLApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.000" Dia x 3.750" L (76.20mm x 95.25mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 1.6kA Voltage Rating - AC 600V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge 600V Cartridge L Cartridge L Cov Bolt A Mount Size / Dimension Cartridge L Cartridge L Cartridge L Cov Cov Bolt A Cov Cartridge L Cov Cov Cov Cov Cov Cartridge Cov Cartridge Cov Cov Cov Cov Cartridge Cov Cartridge Cov Cov Cov Cov Cartridge Cov Cartridge Cov Cov Cov Cov Cartridge Cov Cov Cov Cov Cartridge Cov	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 1.6kA Voltage Rating - AC 600V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.6kA 1.6k	Series	Limitron? KLU
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 600V 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension Slow Slow Slow Slow Slow Slow Slow Slow	Current Rating	1.6kA
Response Time Applications Electrical, Industrial Features - Class L Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Electrical, Industrial CE, CSA, UL Operating Temperature - CE, CSA, UL CE, CSA, UL CURA CE, CSA, UL COBA CURA South Slow CE, CSA, UL CE, CSA, UL COBA CE, CSA, UL COBA CURA South South Slow Slow Slow CE, CSA, UL CE, CSA, UL COBA CE, CSA, UL COBA COBA South Slow Sl	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.750" L (76.20mm x 95.25mm)	Voltage Rating - DC	-
Features - Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.750" L (76.20mm x 95.25mm)	Response Time	Slow
Class L Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.750" L (76.20mm x 95.25mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CE, CSA, UL CULTURE CULTURE CULTURE CULTURE CE, CSA, UL CULTURE CULTURE CULTURE CON CONTROL CE, CSA, UL CULTURE C	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.750" L (76.20mm x 95.25mm)	Class	L
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.750" L (76.20mm x 95.25mm)	Approvals	CE, CSA, UL
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.750" L (76.20mm x 95.25mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.000" Dia x 3.750" L (76.20mm x 95.25mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 3.000" Dia x 3.750" L (76.20mm x 95.25mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	3.000" Dia x 3.750" L (76.20mm x 95.25mm)
		Report errors?

KLU-1600 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KLU-1600 Payment Methods





















KLU-1600 Shipping Methods













If you have any question about KLU-1600, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com