



KMR243GLFG Information



For Reference Only

Part Number KMR243GLFG

Manufacturer C&K **Category** Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.01A 32V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KMR243GLFG Specifications

Manufacturer Part Number KMR243GLFG Manufacturer C&K Category Switches Package - Series KMR2 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.90mm Actuator Height Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection - Features Grounding Pin		
Category Switches Package - Series KMR2 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.90mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection - Features Grounding Pin	Manufacturer Part Number	KMR243GLFG
Package - Series KMR2 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.90mm Actuator Length, Right Angle - Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection - Features Grounding Pin	Manufacturer	C&K
Package	Category	Switches
SeriesKMR2CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.01A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical1.90mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline4.60mm x 2.80mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force400gfIngress Protection-FeaturesGrounding Pin		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.01A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical1.90mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline4.60mm x 2.80mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force400gfIngress Protection-FeaturesGrounding Pin	Package	-
Switch Function Off-Mom Contact Rating @ Voltage 0.01A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.90mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection - Features Grounding Pin	Series	KMR2
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Gundard Standard Standard Standard Standard Standard Surface Mount 1.90mm Actuator Cheman 1.90mm Actuator Length, Right Angle - 4.60mm x 2.80mm Non-Illuminated 1.90mm Actuator Cheman 1.90mm 1.90mm Actuator Cheman 1.90mm 1.90mm Actuator Cheman 1.90mm 1.90mm Actuator Cheman 1.90mm 1.90	Circuit	SPST-NO
Actuator Type Mounting Type Surface Mount Actuator Height off PCB, Vertical 1.90mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force 400gf Ingress Protection Features Grounding Pin	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Gull Wing Outline Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Surface Mount 1.90mm Actuator Mount 1.90mm Actuated Gull Wing Gull Wing A.60mm x 2.80mm Non-Illuminated - 4.60mm x 2.80mm Non-Illuminated - Grounding Pin	Contact Rating @ Voltage	0.01A @ 32VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Ingress Protection Features Grounding Pin	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Gull Wing Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Grounding Pin	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color	Actuator Height off PCB, Vertical	1.90mm
Termination Style Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force 400gf Ingress Protection Features Grounding Pin	Actuator Length, Right Angle	-
Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection - Features Grounding Pin	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force400gfIngress Protection-FeaturesGrounding Pin	Termination Style	Gull Wing
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force400gfIngress Protection-FeaturesGrounding Pin	Outline	4.60mm x 2.80mm
Illumination Voltage (Nominal) - Operating Force 400gf Ingress Protection - Features Grounding Pin	Illumination	Non-Illuminated
Operating Force 400gf Ingress Protection - Features Grounding Pin	Illumination Type, Color	-
Ingress Protection - Grounding Pin	Illumination Voltage (Nominal)	-
Features Grounding Pin	Operating Force	400gf
•	Ingress Protection	-
Report errors?	Features	Grounding Pin
		Report errors?

KMR243GLFG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KMR243GLFG Payment Methods

































If you have any question about KMR243GLFG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com