



KMR421NGLFS Information

Heisener.com

For Reference Only

Part Number KMR421NGLFS

Manufacturer C&K **Category** Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 32V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KMR421NGLFS Specifications

Manufacturer Part Number KMR421NGLFS Manufacturer C&K Category Switches Package - Series KMR4 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 2.50mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection - Features -		
Category Switches Package - Series KMR4 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Surface Mount Mounting Type Surface Mount Actuator Height off PCB, Vertical 2.50mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection - Features -	Manufacturer Part Number	KMR421NGLFS
Package - Series KMR4 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 2.50mm Actuator Length, Right Angle - Contact Ration Style Gull Wing Outline 4.60mm x 2.80mm Illumination Style Gull Wing Illumination Type, Color - Illuminated Illumination Voltage (Nominal) - Coperating Force 200gf Ingress Protection - Features - Commanded - Commanded - Commanded - Commanded - Commanded - Commanded - Coperating Force 200gf Ingress Protection - Commanded - Commanded - Commanded - Commanded - Coperating Force 200gf Ingress Protection - Commanded - Coperating Force 200gf Ingress Protection - Commanded - Com	Manufacturer	C&K
Package - Series KMR4 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 2.50mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection - Features -	Category	Switches
Series KMR4 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 2.50mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection - Features -		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical2.50mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline4.60mm x 2.80mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force200gfIngress Protection-Features-	Package	-
Switch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical2.50mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline4.60mm x 2.80mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force200gfIngress Protection-Features-	Series	KMR4
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 0.05A @ 32VDC Standard Standard Standard Standard Surface Mount 2.50mm Actuator Chemated	Circuit	SPST-NO
Actuator Type Surface Mount Actuator Height off PCB, Vertical 2.50mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection - Features - Standard Standard Standard Standard Sunface Mount 2.50mm Actuator Mount Actuator Orientation - Top Actuated Gull Wing Outline 4.60mm x 2.80mm Non-Illuminated - 200gf - Features - - - - - - - - - - - - -	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Gull Wing Outline Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Surface Mount 2.50mm Surface Mount 2.50mm Actuator Mon-Illuminated Fundamental Surface Mount Actuator Mon-Illuminated Surface Mount 2.50mm Actuator Mon-Illuminated Fundamental Surface Mount Fundamental Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right of Possible Possi	Contact Rating @ Voltage	0.05A @ 32VDC
Actuator Height off PCB, Vertical 2.50mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection - Features -	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Gull Wing Outline 4.60mm x 2.80mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style Gull Wing Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection - Features	Actuator Height off PCB, Vertical	2.50mm
Termination Style Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Gull Wing 4.60mm x 2.80mm Non-Illuminated - 200gf - 100gf	Actuator Length, Right Angle	-
Outline 4.60mm x 2.80mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 200gf Ingress Protection - Features	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force200gfIngress Protection-Features-	Termination Style	Gull Wing
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force200gfIngress Protection-Features-	Outline	4.60mm x 2.80mm
Illumination Voltage (Nominal)-Operating Force200gfIngress Protection-Features-	Illumination	Non-Illuminated
Operating Force 200gf Ingress Protection - Features -	Illumination Type, Color	-
Ingress Protection - Features -	Illumination Voltage (Nominal)	-
Features -	Operating Force	200gf
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

KMR421NGLFS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KMR421NGLFS Payment Methods



















KMR421NGLFS Shipping Methods













If you have any question about KMR421NGLFS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com