



KMT022NGJLHS Information

www.heisener.com

For Reference Only

Part Number KMT022NGJLHS

Manufacturer C&K **Category** Switches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 32V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









KMT022NGJLHS Specifications

Manufacturer Part Number KMT022NGJLHS Manufacturer C&K Category Switches Package - Series KMT0 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.65mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 3.00mm x 2.60mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf Ingress Protection IP68 - Dust Tight, Waterproof		
Category Switches Tactile Switches Package - Series KMT0 Circuit SPST-NO Switch Function Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Orientation Top Actuated Termination Style Outline J Lead Outline J Lead Outline J Lead Outline J Mon-Illuminated Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) - Operating Force J 160gf	Manufacturer Part Number	KMT022NGJLHS
Package - Series KMT0 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.65mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 3.00mm x 2.60mm Illumination Type, Color Illumination Voltage (Nominal) Operating Force 1606	Manufacturer	C&K
Package-SeriesKMT0CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 32VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical0.65mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleJ LeadOutline3.00mm x 2.60mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gf	Category	Switches
Series KMT0 Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.65mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 3.00mm x 2.60mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 160gf		Tactile Switches
Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.65mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 3.00mm x 2.60mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) - Operating Force 160gf	Package	-
Switch Function Contact Rating @ Voltage 0.05A @ 32VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Outline 3.00mm x 2.60mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Off-Mom Onff-Mom Onff-M	Series	KMT0
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 3.00mm x 2.60mm Illumination Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) Operating Force 160gf	Circuit	SPST-NO
Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 0.65mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 3.00mm x 2.60mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf	Switch Function	Off-Mom
Mounting Type Surface Mount Actuator Height off PCB, Vertical O.65mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style J Lead Outline 3.00mm x 2.60mm Illumination Illumination Type, Color Illumination Type, Color - Illumination Voltage (Nominal) Operating Force Surface Mount O.65mm Non-Illumination Top Actuated T	Contact Rating @ Voltage	0.05A @ 32VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style J Lead Outline 3.00mm x 2.60mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Operating Force 160gf	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style J Lead Outline 3.00mm x 2.60mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf	Actuator Height off PCB, Vertical	0.65mm
Termination Style J Lead Outline 3.00mm x 2.60mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf	Actuator Length, Right Angle	-
Outline 3.00mm x 2.60mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force160gf	Termination Style	J Lead
Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 160gf	Outline	3.00mm x 2.60mm
Illumination Voltage (Nominal) - Operating Force 160gf	Illumination	Non-Illuminated
Operating Force 160gf	Illumination Type, Color	-
	Illumination Voltage (Nominal)	-
Ingress Protection IP68 - Dust Tight, Waterproof	Operating Force	160gf
	Ingress Protection	IP68 - Dust Tight, Waterproof
Features Tactile Feedback	Features	Tactile Feedback
Report errors?		Report errors?

KMT022NGJLHS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

KMT022NGJLHS Payment Methods



















KMT022NGJLHS Shipping Methods













If you have any question about KMT022NGJLHS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com