

# KO130QA136

# **KO130QA136 Information**

Heisener.com	Part Number Manufacturer Category Description Package	KO130QA136 E-Switch Switches Keylock Switches SWITCH KEYLOCK 2POS DPDT 4A 125V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **KO130QA136** Specifications

Manufacturer Part NumberKO130QA136Manufacturer RateE-SwitchCategorySwitchesPackage-SeriesKOCircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingA(AC)Voltage Rating - AC125VVoltage Rating - DCSoilyActuar TypeSoilyAngle of ThrowSoilyContact FunishSoilyContact Timing-Cottact TimingCorper AlloyCottact TimeSoilyCottact TimeSoilyCottact TimeSoilyCottact TimeSoilyCottact TimeSoilyCottact TimeSoilyCottact TimeSoilyActuar TypeSoilyCottact MaterialSoilyContact TimishSoilyContact TimishSoilyCottact Timish <td< th=""><th></th><th></th></td<>		
CategorySwitchesPackage-SeriesKOCircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingAd (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator Type5 onlyAngle of Throw90°Contact FinishGoper AlloyContact FinishSilverMounting TypeSolder LugMounting TypeSolder LugFeaturesSolder LugFeaturesSolder Lug	Manufacturer Part Number	K0130QA136
Keylock SwitchesPackage-SeriesKOCircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyOntact Timing00°Contact TimingGoper AlloyContact TimingSilverAngle of ThrowSilverMounting TypeSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Manufacturer	E-Switch
Package-SeriesKOCircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingMot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of ThrowCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Features-	Category	Switches
SeriesKOCircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingMot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-		Keylock Switches
CircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyRemovable Positions5 onlyAngle of Throw90°Contact FinishSilverMounting TypePanel MountFarmination StyleSolder LugPanel Cutout DimensionsCircular 19.00mm DiaFeatures-	Package	-
Number of Positions2Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialSilverMounting TypePanel MountFarmination StyleSolder LugPanel Cutout DimensionsCircular 19.00mm DiaFeatures-	Series	КО
Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialSilverContact FinishSilverMounting TypePanel MountPanel Cutout DimensionsSilverFeaturesSilver JournantFeaturesSilver Journant<	Circuit	DPDT
Contact TimingNot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact FinishGoper AlloyMounting TypeSilverFermination StyleSolder LugPanel Cutout DimensionsSolder LugFeaturesCroutant PlaneFeaturesSilverPanel Cutout DimensionsSolder LugFeatures-StatemensionsSilverFeatures<	Number of Positions	2
Current Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Switch Function	On-On
Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Contact Timing	Not Specified
Voltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Current Rating	4A (AC)
Actuator TypeFlat KeyActuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Voltage Rating - AC	125V
Key Removable Positions5 onlyAngle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Voltage Rating - DC	-
Angle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Actuator Type	Flat Key
Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Key Removable Positions	5 only
Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Angle of Throw	90°
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Contact Material	Copper Alloy
Termination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Contact Finish	Silver
Panel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Mounting Type	Panel Mount
Features -	Termination Style	Solder Lug
	Panel Cutout Dimensions	Circular - 19.00mm Dia
Report errors?	Features	-
		Report errors?

#### **KO130QA136** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **KO130QA136 Payment Methods**



## KO130QA136 Shipping Methods



If you have any question about KO130QA136, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com