

# KO130QA138

# **KO130QA138 Information**

Heisener.com	Part Number Manufacturer Category Description Package	KO130QA138 E-Switch Switches Keylock Switches SWITCH KEYLOCK 2POS DPDT 4A 125V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **KO130QA138** Specifications

Manufacturer Part NumberKO130QA138Manufacturer QE-SwitchCategorySwitchesPackage-SeriesKOCircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingA(AC)Voltage Rating - AC125VVoltage Rating - DCSonlyActuar TypeSonlyAngle of ThrowSonlyContact FinishSonlyAngle of ThrowSonlyContact FinishSonlyAngle of ThrowSonlyContact FinishSilverMounting TypeSolder LugContact FinishSolder LugPanel MountSolder LugPanel Mount DimensionsCircular 19.00mm DiaFatures-		
Switches   Package -   Series KO   Circuit DPDT   Number of Positions 2   Switch Function OnOn   Contact Timing Not Specified   Outrent Rating 4A (AC)   Voltage Rating - AC 125V   Voltage Rating - DC -   Actuator Type Sonly   Angle of Throw 90°   Contact Finish Goper Alloy   Angle of Throw Soller Lug   Mounting Type Soller Lug   Actuator Type Soller Lug   Final Material Sclorer Alloy   Angle of Throw Corper Alloy   Angle of Throw Soller Lug   Final Material Sclorer Alloy   Angle of Throw Soller Lug   Angle Of Lug Soller Lug   Mounting Type Soller Lug   Anall Cutout Dimensions Soller Lug	Manufacturer Part Number	K0130QA138
Keylock SwitchesPackage-SeriesKOCircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyContact Timing00°Contact TimingGoper AlloyContact TimeSilverAngle of ThrowSilverMounting TypeSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Manufacturer	E-Switch
Package-SeriesKOCircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingMot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyContact TiningCopper AlloyContact TiningSilverAngle of ThrowSilverContact FinishSolder LugMounting TypeSolder LugFareniation StyleSolder LugFatures-	Category	Switches
SeriesKOCircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingMot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of ThrowOoper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-		Keylock Switches
CircuitDPDTNumber of Positions2Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyRemovable Positions5 onlyAngle of Throw90°Contact FinishSilverMounting TypePael MountTermination StyleSolder LugPanel Cutout DimensionsCircular 19.00mm DiaFeatures-	Package	-
Number of Positions2Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Series	КО
Switch FunctionOn-OnContact TimingNot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialSilverContact FinishSilverMounting TypePanel MountPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Circuit	DPDT
Contact TimingNot SpecifiedCurrent Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact FinishSilverMounting TypeSolder LugPremination StyleSolder LugPanel Cutour DimensionsSolder LugFeatures-Features-	Number of Positions	2
Current Rating4A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Switch Function	On-On
Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular 19.00mm DiaFeatures-	Contact Timing	Not Specified
Voltage Rating - DC-Actuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Current Rating	4A (AC)
Actuator TypeFlat KeyActuator TypeFlat KeyKey Removable Positions5 onlyAngle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Voltage Rating - AC	125V
Key Removable Positions5 onlyAngle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Voltage Rating - DC	-
Angle of Throw90°Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Actuator Type	Flat Key
Contact MaterialCopper AlloyContact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Key Removable Positions	5 only
Contact FinishSilverMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Angle of Throw	90°
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Contact Material	Copper Alloy
Termination StyleSolder LugPanel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Contact Finish	Silver
Panel Cutout DimensionsCircular - 19.00mm DiaFeatures-	Mounting Type	Panel Mount
Features -	Termination Style	Solder Lug
	Panel Cutout Dimensions	Circular - 19.00mm Dia
Report errors?	Features	-
		Report errors?

#### **KO130QA138** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **KO130QA138 Payment Methods**



## KO130QA138 Shipping Methods



If you have any question about KO130QA138, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com